

ASSURANCE ACTIVITY REPORT

Adder AVS-4228, AVS-42216 and XDS441, XDS441FX Firmware Version 44404-E7E7 Peripheral Sharing Devices

PREPARED BY

EWA-Canada, An Intertek Company

PREPARED FOR

Communications Security Establishment (CSE) and
National Information Assurance Partnership (NIAP)

REPORT NO

2149-005-D007-2

DOCUMENT VERSION

Version 1.9

DATE

7 December 2022





Contents

1	INTRODUCTION	1
1.1	EVIDENCE	1
1.2	REFERENCES.....	1
2	SECURITY FUNCTIONAL REQUIREMENT ASSURANCE ACTIVITIES.....	3
2.1	USER DATA PROTECTION (FDP)	3
2.1.1	FDP_APC_EXT.1 Active PSD Connections	3
2.1.2	FDP_APC_EXT.1/KM Active PSD Connections	4
2.1.3	FDP_APC_EXT.1/VI Active PSD Connections	13
2.1.4	FDP_PDC_EXT.1 Peripheral Device Connection	22
2.1.5	FDP_PDC_EXT.2/KM Authorized Devices (Keyboard/Mouse).....	28
2.1.6	FDP_PDC_EXT.3/KM Authorized Connection Protocols (Keyboard/Mouse)	29
2.1.7	FDP_PDC_EXT.2/VI Peripheral Device Connection (Video Output).....	30
2.1.8	FDP_PDC_EXT.3/VI Authorized Connection Protocols (Video Output).....	32
2.1.9	FDP_SWI_EXT.1 PSD Switching.....	33
2.1.10	FDP_RIP_EXT.1 Residual Information Protection	34
2.1.11	FDP_UDF_EXT.1/KM Unidirectional Data Flow (Keyboard/Mouse).....	34
2.1.12	FDP_UDF_EXT.1/VI Unidirectional Data Flow (Video Output)	35
2.2	PROTECTION OF THE TSF (FPT)	36
2.2.1	FPT_FLS_EXT.1 Failure with Preservation of Secure State	36
2.2.2	FPT_NTA_EXT.1 PSD No Access to TOE	36
2.2.3	FPT_PHP.1 Passive Detection of Physical Attack.....	37
2.2.4	FPT_TST.1 TSF Testing	38
2.2.5	FPT_TST_EXT.1 TSF Testing	41
3	EVALUATION ACTIVITIES FOR OPTIONAL REQUIREMENTS.....	42
3.1	USER DATA PROTECTION (FDP)	42
3.1.1	FDP_FIL_EXT.1/KM Device Filtering (Keyboard/Mouse).....	42
3.1.2	FDP_RDR_EXT.1 Re-Enumeration Device Rejection	44
4	SELECTION-BASED REQUIREMENTS	46
4.1	USER DATA PROTECTION (FDP)	46
4.1.1	FDP_CDS_EXT.1 Connected Displays Supported	46
4.1.2	FDP_IPC_EXT.1 Internal Protocol Conversion	47



4.1.3	FDP_SWI_EXT.3 Tied Switching	47
4.1.4	FDP_RIP.1/KM Residual Information Protection (Keyboard Data).....	48
4.1.5	FDP_SPR_EXT.1/DP Sub-Protocol Rules (DisplayPort Protocol)	49
4.1.6	FDP_SPR_EXT.1/HDMI Sub-Protocol Rules (HDMI Protocol)	50
4.1.7	FDP_SWI_EXT.2 PSD Switching Methods	51
4.2	TOE ACCESS (FTA)	53
4.2.1	FTA_CIN_EXT.1 Continuous Indications	53
5	SECURITY ASSURANCE REQUIREMENT ACTIVITIES	55
5.1	DEVELOPMENT (ADV)	55
5.1.1	ADV_FSP.1 Basic Functional Specifications	55
5.2	GUIDANCE DOCUMENTS (AGD).....	55
5.2.1	AGD_OPE.1 Operational User Guidance	55
5.2.2	AGD_PRE.1 Preparative Procedures.....	56
5.3	LIFE-CYCLE SUPPORT (ALC)	56
5.3.1	ALC_CMC.1 Labeling of the TOE	56
5.3.2	ALC_CMS.1 TOE CM Coverage.....	56
5.4	TESTS (ATE)	57
5.4.1	ATE_IND Independent Testing - Conformance.....	57
5.5	VULNERABILITY ANALYSIS (AVA).....	57
5.5.1	AVA_VAN.1 Vulnerability Survey.....	57



The Developer of the TOE:

Adder Technology
Saxon Way Bar Hill
Cambridge, United Kingdom,
CB23 8SL

Common Criteria Versions

- Common Criteria for Information Technology Security Evaluation Part 1: Introduction, Version 3.1, Revision 5, April 2017.
- Common Criteria for Information Technology Security Evaluation Part 2: Security Functional Components, Version 3.1, Revision 5, April 2017.
- Common Criteria for Information Technology Security Evaluation Part 3: Security Assurance Components, Version 3.1, Revision 5, April 2017.

Common Evaluation Methodology Versions

- Common Methodology for Information Technology Security Evaluation, Evaluation Methodology, Version 3.1, Revision 5, April 2017.

Protection Profiles

- Protection Profile for Peripheral Sharing Device, 2019-07-19, Version 4.0
- PP-Module for Keyboard/Mouse Devices, 2019-07-19, Version 1.0
- PP-Module for Video/Display Devices, 2019-07-19, Version 1.0
- PP-Configuration for Peripheral Sharing Device, Keyboard/Mouse Devices, and Video/Display Devices, 19 July 2019, Version 1.0

NIAP Technical Decisions

ITEM	TECHNICAL DECISION TITLE
TD0506	Missing steps to connect and reconnect display [MOD_VI_V1.0]
TD0507	Clarification on USB plug type [MOD_KM_V1.0]
TD0514	Correction to MOD_VI FDP_APC_EXT.1 Test 3 Step 6 [MOD_VI_V1.0]
TD0518	Typographical error in Dependency Table [PP_PSD_V4.0]
TD0539	Incorrect selection trigger in FTA_CIN_EXT.1 in [MOD_VI_V1.0]
TD0583	FPT_PHP.3 modified for PSD remote controllers [PP_PSD_V4.0]



ITEM	TECHNICAL DECISION TITLE
TD0584	Update to FDP_APC_EXT.1 Video Tests [MOD_VI_V1.0]
TD0586	DisplayPort and HDMI Interfaces in FDP_IPC_EXT.1 [MOD_VI_V1.0]
TD0593	Equivalency Arguments for PSD [MOD_KM_V1.0], [MOD_VI_V1.0]
TD0620	EDID Read Requirements [MOD_VI_V1.0]

Table 1 – NIAP Technical Decisions



1 Introduction

This document presents assurance activity evaluation results of the TOE evaluation. There are three types of assurance activities and the following is provided for each:

1. TOE Summary Specification (TSS) - An indication that the required information is in the TSS section of the Security Target;
2. Guidance - A specific reference to the location in the guidance is provided for the required information; and
3. Test – A summary of the test procedure used and the results obtained is provided for each required test activity.

This Assurance Activities Report contains sections for each functional class and family and sub-sections addressing each of the SFRs specified in the Security Target. The SARs are also addressed.

1.1 Evidence

The following is a list of the documents consulted:

- [ST] Adder AVS-4228, AVS-42216, XDS441, XDS441FX Firmware Version 44404-E7E7 Peripheral Sharing Devices Security Target, version 1.6, 7 December 2022
- [CC_Supp] Adder AVS-4228, AVS-42216, XDS441, XDS441FX Firmware Version 44404-E7E7 Peripheral Sharing Devices Common Criteria Guidance Supplement, v1.3, 12 October 2021
- [Isol] Adder AVS-4228, AVS-42216, XDS441, XDS441FX Firmware Version 44404-E7E7 Peripheral Sharing Devices Isolation Document, version 1.3, 12 October 2021
- [QS-000040] ADDERView™ Secure 4, 8 and 16-Port High Security 4K Multi-Viewer Switches, Quick Start, MAN-QS-000040_V0-1 RC2
- [QS-000045] ADDERView™ Secure 4 and 8-Port Remote Control Units, Quick Start, MAN-QS-000045_V0-1 RC1
- [QS-000047] ADDERView™ Secure 4K KVM Extenders, Quick Start, MAN-QS-000047_V0-1 RC1
- [ETProcRes] Evaluation Test Plan, Procedures and Results for Peripheral Sharing Device Version 4.0 Common Criteria Evaluation of Adder CFG_PSD-KM-VI, version 1.6, 7 December 2022

1.2 References

- [PP_PSD_V4.0] Protection Profile for Peripheral Sharing Device, 2019-07-19, Version 4.0
- [MOD_KM_V1.0] PP-Module for Keyboard/Mouse Devices, 2019-07-19, Version 1.0
- [MOD_KM_SD] Supporting Document, PP-Module for Keyboard/Mouse Devices, 2019-07-19, Version 1.0
- [MOD_VI_V1.0] PP-Module for Video/Display Devices, 2019-07-19, Version 1.0



- [MOD_VI_SD] Supporting Document, PP-Module for Video/Display Devices, 2019-07-19, Version 1.0



2 Security Functional Requirement Assurance Activities

2.1 User Data Protection (FDP)

2.1.1 FDP_APC_EXT.1 Active PSD Connections

2.1.1.1 FDP_APC_EXT.1.1

The TSF shall route user data only to or from the interfaces selected by the user.

Evaluation activities are detailed below.

2.1.1.2 FDP_APC_EXT.1.2

The TSF shall ensure that no data flows between connected computers whether the TOE is powered on or powered off.

Evaluation activities are detailed below.

2.1.1.3 FDP_APC_EXT.1.3

The TSF shall ensure that no data transits the TOE when the TOE is powered off.

Evaluation activities are detailed below.

2.1.1.4 FDP_APC_EXT.1.4

The TSF shall ensure that no data transits the TOE when the TOE is in a failure state.

Evaluation Activity

Isolation Document

The evaluator shall review the Isolation Documentation and Assessment as described in Appendix D of this PP and ensure that it adequately describes the isolation concepts and implementation in the TOE and why it can be relied upon to provide proper isolation between connected computers whether the TOE is powered on or powered off.

TSS

The evaluator shall verify that the TSS describes the conditions under which the TOE enters a failure state.

Guidance

The evaluator shall verify that the operational user guidance describes how a user knows when the TOE enters a failure state.

Test

There are no test Evaluation Activities for this component.

Isolation Document Evaluator Assessment:

The [Isol] was reviewed. The document adequately describes the proper isolation whether the TOE is powered on or not. A complete review of this document is in the file “CFG_PSD-KM-VI - Annex D Adder Isolation Documentation assessment”.

TSS Evaluator Assessment:

The TSS discusses the conditions under which the TOE enters a failure state due to self-test failure in section 9.2.3 of the [ST]. “The TOE performs a self-test at initial start-up. The self-test runs independently on the microcontroller and performs verification of the integrity of the microcontroller firmware. On the AVS-4228 and AVS-42216 devices, the self-test also performs the following checks:



- Verification of the front panel push-buttons
- Verification of computer port isolation. This is tested by sending test packets to various interfaces and attempting to detect this traffic at all other interfaces

If the self-test fails, the LEDs on the front panel blink to indicate the failure. The AVS-4228 and AVS-42216 devices also make a clicking sound, and the TOE disables the PSD switching functionality. In all cases, the TOE disables the data flow functionality and remains in a disabled state until the self-test is rerun and passes.”

Guidance Evaluator Assessment:

The [QS-000040] and section 4.2 of the [CC_Supp] were reviewed. The documents adequately describe how a user will know when the TOE enters a failure state. As per Section 4.2 of [CC_Supp] “As the product powers up, it performs a self-test procedure. Following failure of a self-test, the device will enter an error state. The error state is indicated by sequential flashing of the Light Emitting Diodes. The combiner devices will also make a clicking noise. At this point, the device will be inoperable. It will not accept input from any peripheral device or pass output to any peripheral device.”

Test Evaluator Assessment:

Not applicable

2.1.2 FDP_APC_EXT.1/KM Active PSD Connections

2.1.2.1 FDP_APC_EXT.1.1/KM

The TSF shall route user data only to the interfaces selected by the user.

Evaluation activities are detailed below.

2.1.2.2 FDP_APC_EXT.1.2/KM

The TSF shall ensure that no data or electrical signals flow between connected computers whether the TOE is powered on or powered off.

Evaluation activities are detailed below.

2.1.2.3 FDP_APC_EXT.1.3/KM

The TSF shall ensure that no data transits the TOE when the TOE is powered off.

Evaluation activities are detailed below.

2.1.2.4 FDP_APC_EXT.1.4/KM

The TSF shall ensure that no data transits the TOE when the TOE is in a failure state.

Application Note

This SFR is refined from the PSD PP for this PP-Module to include further restrictions for electrical signals. It is unlikely that this element can be satisfied unless mouse and keyboard peripheral device interfaces are electrically and logically isolated from the connected computer interfaces or through other methods, such as USB host and USB device emulation.

For TOEs that support only a keyboard or mouse, but not both, tests and portions of tests that involve using the non-supported peripheral are considered conditional.



If the TOE claims conformance to multiple PP-Modules, each PP-Module modifies this SFR in a different manner for the interfaces that are unique to that module. In this case, the ST author should reference this modification of the SFR as “FDP_APC_EXT.1/KM” for uniqueness. Note that all elements of FDP_APC_EXT.1 must be included in this iteration, not just the ones that are modified by this PP-Module.

Evaluation Activity

Isolation Document

The evaluator shall examine the Isolation Document and verify it describes how the TOE ensures that no data or electrical signals flow between connected computers in both cases (powered on, powered off).

TSS

There are no TSS EAs for this component beyond what the PSD PP requires.

Guidance

There are no guidance EAs for this component beyond what the PSD PP requires.

Test

For tests that use the USB sniffer or USB analyzer software, the evaluator verifies whether traffic is sent or not sent by inspection of the passing USB transactions and ensuring they do not contain USB data payloads other than any expected traffic, as well as USB NAK transactions or system messages. To avoid clutter during USB traffic capture, the evaluator may filter NAK transactions and system messages.

The evaluator shall perform the following tests:

Test 1-KM – KM Switching methods

[Conditional: Perform this test if “switching can be initiated only through express user action” is selected in FDP_SWI_EXT.1.1 in the PSD PP]

While performing this test, ensure that switching is always initiated through express user action.

This test verifies the functionality of the TOE’s KM switching methods.

Step 1: Configure the TOE and the Operational Environment in accordance with the operational guidance. Connect an authorized peripheral device for each peripheral device type selected in FDP_PDC_EXT.3.1/KM. Run an instance of a text editor on each connected computer.

Step 2: Connect a display to each computer in order to see all computers at the same time, turn on the TOE, and enter text or move the cursor to verify which connected computer is selected.

Step 3: For each switching method selected in FDP_SWI_EXT.2.2, switch selected computers in accordance with the operational user guidance, and verify that it succeeds.

Step 4: For each peripheral device type selected in FDP_PDC_EXT.3.1/KM, attempt to switch the device to more than one computer at once and verify that the TOE ignores all such commands or otherwise prevents the operation from executing.

Step 5: [Conditional: If “keyboard” is selected in FDP_PDC_EXT.3.1/KM, then] attempt to control the computer selection using the following standard keyboard shortcuts, where ‘#’ represents a computer channel number, and verify that the selected computer is not switched:

- Control - Control - # - Enter

- Shift - Shift - #

- Num Lock - Minus - #

- Scroll Lock - Scroll Lock - #



- Scroll Lock - Scroll Lock - Function #

- Scroll Lock - Scroll Lock - arrow (up or down)

- Scroll Lock - Scroll Lock - # - enter

- Control - Shift - Alt - # - Enter

- Alt - Control - Shift - #

Step 6: [Conditional: If "mouse" is selected in FDP_PDC_EXT.3.1/KM, then] attempt to switch to other connected computers using the pointing device and verify that it does not succeed.

Step 7: [Conditional: If "peripheral devices using a guard" is selected in FDP_SWI_EXT.2.2, then] attempt to switch to other connected computers using the peripheral device and guard by only performing some of the steps outlined in the operational user guidance, and verify that it does not succeed.

Test 2-KM – Positive and Negative Keyboard and Mouse Data Flow Rules Testing

This test verifies the functionality for correct data flows of a mouse and keyboard during different power states of the selected computer.

Step 1: Continue with the test setup from Test 1 and for each connected computer, connect a USB sniffer between it and the TOE or open the USB analyzer software. Perform steps 2-12 with each connected computer as the selected computer.

Step 2: Exercise the functions of the peripheral device type selected in FDP_PDC_EXT.3.1/KM and verify that the expected results are observed on the selected computer and that the expected traffic is sent and captured using the USB analyzer.

[Conditional: Perform steps 3-10 if "switching can be initiated only through express user action" is selected in FDP_SWI_EXT.1.1 in the PSD PP.]

Step 3: [If "mouse" is selected in FDP_PDC_EXT.3.1/KM, then] switch the TOE to each connected computer, and use the mouse to position the mouse cursor at the center of each display. Switch the TOE back to the originally selected computer.

Step 4: [If "keyboard" is selected in FDP_PDC_EXT.3.1/KM, then] use the keyboard to enter text into the text editor. [If "mouse" is selected in FDP_PDC_EXT.3.1/KM, then] use the mouse to move the cursor to the bottom right corner of the display.

Step 5: Switch to each connected computer and verify that the actions taken in Step 4 did not occur on any of the non-selected computers.

Step 6: Switch to the originally selected computer. Continue exercising the functions of the peripheral device(s) and examine the USB protocol analyzers on each one of the non-selected computers and verify that no traffic is sent.

Step 7: Disconnect and reconnect the TOE interface cables connected to the selected computer. Examine the USB protocol analyzers on each one of the non-selected computers and verify that no traffic is sent.

Step 8: Reboot the selected computer. Examine the USB protocol analyzers on each one of the nonselected computers and verify that no traffic is sent.

Step 9: Enter sleep or suspend mode in the selected computer. Examine the USB protocol analyzers on each one of the non-selected computers to verify that no traffic is sent.

Step 10: Exit sleep or suspend mode on the selected computer. Examine the USB protocol analyzers on each of the non-selected computers to verify that no traffic is sent. Ensure that any text in the Text Editor application is deleted.

Step 11: Perform step 12 when the TOE is off and then in a failure state.

Step 12: Exercise the functions of the peripheral device type selected in FDP_PDC_EXT.3.1/KM and verify that no results are observed on the selected computer and that no traffic is captured using the USB analyzer.

Test 3-KM – Flow Isolation and Unidirectional Rule

This test verifies that the TOE properly enforces unidirectional flow and isolation.

Step 1: Ensure the TOE and the Operational Environment are configured in accordance with the operational guidance.

Perform steps 2-12 with each connected computer as the selected computer.



Step 2: Ensure the TOE is powered on and connect a display directly to the selected computer. Open a real-time hardware information console on the selected computer.

[If "mouse" is selected in FDP_PDC_EXT.3.1/KM, then perform steps 3-4]

Step 3: Connect a gaming mouse with programmable LEDs directly to the selected computer and attempt to configure the LEDs using the mouse application running on the selected computer. Verify that the mouse programmable LEDs change state.

Step 4: Disconnect the gaming mouse from the selected computer and connect it to the TOE mouse peripheral device port through the USB sniffer. Attempt to configure the LEDs using the mouse application running on the selected computer. Verify that the mouse programmable LEDs do not change state and that no traffic is sent and captured by the USB sniffer while the evaluator is not moving the mouse.

[If "keyboard" is selected in FDP_PDC_EXT.3.1/KM, then perform step 5]

Step 5: Connect a keyboard to the peripheral device interface through the USB sniffer. Use a keyboard emulation software application running on the selected computer to turn the keyboard Num Lock, Caps Lock, and Scroll Lock LEDs on and off. Verify that the LEDs on the keyboard do not change state and that no traffic is sent and captured by the USB sniffer.

Step 6: Power down the TOE and disconnect the peripheral interface USB cable from the TOE to the selected computer and the peripheral devices from the TOE.

Step 7: Power up the TOE and ensure the selected computer has not changed (this should have no effect on the selected computer because it was disconnected in the previous step). Reconnect the peripheral devices disconnected in step 6 to the TOE.

Step 8: [If "mouse" is selected in FDP_PDC_EXT.3.1/KM, then] check that immediately following the connection, the mouse LEDs are illuminated (indicating that the peripheral devices are powered on, although the selected computer is not connected). [If "keyboard" is selected in FDP_PDC_EXT.3.1/KM, then] check that immediately following the connection, the Num Lock, Caps Lock, and Scroll Lock keyboard LEDs are blinking momentarily and then stay off (indicating that the keyboard is powered on, although the selected computer is not connected).

Step 9: Turn the TOE off and disconnect the peripheral devices connected in step 6.

Step 10: Reconnect the first computer interface USB cable to the TOE.

Step 11: Turn on the TOE and check the computer real-time hardware information console for the presence of the peripheral devices connected in step 6 and disconnected in step 9. The presence of the TOE peripheral devices in the information console when the peripheral devices are not connected to the TOE indicates that the TOE emulates the KM devices.

Step 12: [Conditional] If the TOE keyboard and mouse do not appear in the listed devices, repeat the following steps for both mouse and keyboard to simulate USB traffic:

- Connect a USB generator to the TOE peripheral device interface port.

- Configure the USB generator to enumerate as a generic HID mouse/keyboard device and then to generate a random stream of mouse/keyboard report packets.

- Connect a USB sniffer device between the TOE computer interface and the USB port on the first computer to capture the USB traffic between the TOE and the first computer.

- Turn on the TOE and verify that no packets cross the TOE following the device enumeration.

Test 4-KM – No Flow between Computer Interfaces

[Conditional: Perform this test if "switching can be initiated only through express user action" is selected in FDP_SWI_EXT.1.1 in the PSD PP].

This test verifies correct data flow while the TOE is powered on or powered off.

Step 1: Ensure the TOE and the Operational Environment are configured in accordance with the operational guidance. Connect a display directly to each connected computer. Perform steps 2-10 for each connected computer.

Step 2: Connect a USB sniffer between a non-selected TOE KM computer interface and its computer. Run USB protocol analyzer software on all remaining computers.



Step 3: Turn on the TOE and observe the TOE enumeration data flow in the protocol analyzer connected to the selected computer and is not in any other USB protocol analyzers or the USB sniffer.

Step 4: Ensure the TOE is switched to the first computer.

Step 5: Reboot the first computer. Verify that no USB traffic is captured on all non-selected computer USB protocol analyzers.

Step 6: Generate intensive USB HID traffic by moving the mouse at high speed and/or holding down the keyboard space key at the same time. Verify that no new USB traffic is captured on all non-selected computer USB protocol analyzers.

Step 7: Perform steps 8 and 9 for each TOE keyboard/mouse peripheral interface.

Step 8: Connect a USB dummy load into the TOE KM peripheral device interface. Verify that no new USB traffic is captured on all non-selected computer USB protocol analyzers. Remove the plug after the step is completed.

*Step 9: Connect a switchable 5-volt power supply with any compatible USB plug into the TOE KM peripheral device interface. Modulate the 5-volt supply (i.e., cycle on and off) manually at various speeds from approximately one cycle per five seconds to one cycle per second. Verify that no new USB traffic is captured on all non-selected computer USB analyzers. **Note: TD0507 applied***

Step 10: Turn off the TOE. Verify that no new traffic is captured.

Test 5-KM – No Flow between Connected Computers over Time

This test verifies that the TOE does not send data to different computers connected to the same interface at different times. Repeat this test for each TOE KM computer port.

Step 1: Configure the TOE and the Operational Environment in accordance with the operational guidance. Connect an authorized peripheral device for each peripheral device type selected in FDP_PDC_EXT.3.1/KM. Connect two computers to a different display and run an instance of a text editor and USB analyzer software on each computer.

Step 2: Connect the first computer to the TOE and ensure it is selected and that no other computers are connected.

Step 3: Exercise the functions of the peripheral device type selected in FDP_PDC_EXT.3.1/KM and verify that the expected results are observed on the selected computer and that the expected traffic is sent and captured using the USB analyzer.

Step 4: Disconnect the first computer. Generate intensive USB HID traffic by moving the mouse at high speed and/or holding down the keyboard space key at the same time.

Step 5: Cease generation of the USB HID traffic, connect the second computer to the same port and ensure it is selected.

Step 6: Verify that no results from the previous use of the peripheral device are observed on the selected computer and that no traffic is sent and captured using the USB analyzer.

Step 7: Reboot the TOE and repeat step 6.

Step 8: Turn off the TOE and repeat step 6.

Step 9: Restart the TOE and repeat step 6.

Step 10: Exercise the functions of the peripheral device type selected in FDP_PDC_EXT.3.1/KM and verify that the expected results are observed on the selected computer and that the expected traffic is sent and captured using the USB analyzer.

Isolation Document Evaluator Assessment:

[Isol] Figure 1 illustrates all possible data flows for combiners and figure 2 shows all possible data flows for isolators. There follows Table 1 Data Flow Description for Combiners, that gives an explanation of all data flows for combiners and Table 2 Data Flow Description for Isolator Devices, which explains the data flows for isolators. Figures 1 and 2 which characterize the data flows various parts of the TOE (i.e. combiners, isolators) are part of the isolation justification and indicate the methods used to maintain the data separation. Section 2.3 of [Isol] gives an explanation of power isolation. Section 2.4 discusses programmable components. Section 3 describes the isolation enforcement policy for various aspects of the TOE. Figures 5, 7 and 8 show the policy enforcement and figure 6 shows the physical characteristics.

A complete analysis of the Isolation document is found in the file CFG_PSD-KM-VI - Annex D Adder Isolation Documentation assessment.doc.



TSS Evaluator Assessment:

Not applicable

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Test 1

This test is only applicable for the AVS-4228 and AVS-42216 models. The condition “Switching can be initiated only through express user action” in FDP_SWI_EXT.1.1 is selected for the AVS-4228 and AVS-42216 models. The condition “the TOE supports only one connected computer” in FDP_SWI_EXT.1.1 is selected for the XDS441 and XDS441FX models.

1. Configure the TOE and the Operational Environment in accordance with the operational guidance. Connect an authorized peripheral device for each peripheral device type selected in FDP_PDC_EXT.3.1/KM. Run an instance of a text editor on each connected computer.
2. Connect a display to each computer in order to see all computers at the same time, turn on the TOE, and enter text or move the cursor to verify which connected computer is selected.
3. For each switching method selected in FDP_SWI_EXT.2.2, switch selected computers in accordance with the operational user guidance, and verify that it succeeds.
4. For each peripheral device type selected in FDP_PDC_EXT.3.1/KM, attempt to switch the device to more than one computer at once and verify that the TOE ignores all such commands or otherwise prevents the operation from executing.
5. [Conditional: If “keyboard” is selected in FDP_PDC_EXT.3.1/KM, then] attempt to control the computer selection using the following standard keyboard shortcuts, where ‘#’ represents a computer channel number, and verify that the selected computer is not switched:
 - Control - Control - # - Enter
 - Shift - Shift - #
 - Num Lock - Minus - #
 - Scroll Lock - Scroll Lock - #
 - Scroll Lock - Scroll Lock - Function #
 - Scroll Lock - Scroll Lock - arrow (up or down)
 - Scroll Lock - Scroll Lock - # - enter
 - Control - Shift - Alt - # - Enter
 - Alt - Control - Shift - #
6. [Conditional: If “mouse” is selected in FDP_PDC_EXT.3.1/KM, then] attempt to switch to other connected computers using the pointing device and verify that it does not succeed.
7. [Conditional: If “peripheral devices using a guard” is selected in FDP_SWI_EXT.2.2, then] attempt to switch to other connected computers using the peripheral device and guard by only performing some of the steps outlined in the operational user guidance, and verify that it does not succeed.

The functionality of the TOE’s KM switching methods has been tested successfully. The evaluator has confirmed that the TOE prevents the user from switching between more than one computer at once.

Units Tested	AVS-4228
--------------	-----------------



Result	PASS
--------	------

Test 2

1. Continue with the test setup from Test 1 and for each connected computer, connect a USB sniffer between it and the TOE or open the USB analyzer software. Perform steps 2-12 with each connected computer as the selected computer.
2. Exercise the functions of the peripheral device type selected in FDP_PDC_EXT.3.1/KM and verify that the expected results are observed on the selected computer and that the expected traffic is sent and captured using the USB analyzer.

“Switching can be initiated only through express user action” is selected in FDP_SWI_EXT.1.1 for the AVS-4228. Therefore, steps 3-10 were only executed on AVS-4228.

3. *[Conditional: Perform steps 3-10 if “switching can be initiated only through express user action” is selected in FDP_SWI_EXT.1.1 in the PSD PP.]* [If “mouse” is selected in FDP_PDC_EXT.3.1/KM, then] switch the TOE to each connected computer and use the mouse to position the mouse cursor at the center of each display. Switch the TOE back to the originally selected computer.
4. [If “keyboard is selected in FDP_PDC_EXT.3.1/KM, then] use the keyboard to enter text into the text editor. [If “mouse” is selected in FDP_PDC_EXT.3.1/KM, then] use the mouse to move the cursor to the bottom right corner of the display.
5. Switch to each connected computer and verify that the actions taken in Step 4 did not occur on any of the non-selected computers.
6. Switch to the originally selected computer. Continue exercising the functions of the peripheral device(s) and examine the USB protocol analyzers on each one of the non-selected computers and verify that no traffic is sent.
7. Disconnect and reconnect the TOE interface cables connected to the selected computer. Examine the USB protocol analyzers on each one of the non-selected computers and verify that no traffic is sent.
8. Reboot the selected computer. Examine the USB protocol analyzers on each one of the non-selected computers and verify that no traffic is sent.
9. Enter sleep or suspend mode in the selected computer. Examine the USB protocol analyzers on each one of the non-selected computers to verify that no traffic is sent.
10. Exit sleep or suspend mode on the selected computer. Examine the USB protocol analyzers on each of the non-selected computers to verify that no traffic is sent. Ensure that any text in the Text Editor application is deleted.
11. Perform step 12 when the TOE is off and then in a failure state.
12. Exercise the functions of the peripheral device type selected in FDP_PDC_EXT.3.1/KM and verify that no results are observed on the selected computer and that no traffic is captured using the USB analyzer.

Correct data flows of a mouse and keyboard during different power states of the selected computer has been tested. The evaluator has confirmed that data flow is transmitted to the correct computers at the accurate times.

Units Tested	AVS-4228, XDS441FX (steps 1 & 2)
Result	PASS



Test 3

1. Ensure the TOE and the Operational Environment are configured in accordance with the operational guidance.
2. Ensure the TOE is powered on and connect a display directly to the selected computer. Open a real-time hardware information console on the selected computer.
3. Connect a gaming mouse with programmable LEDs directly to the selected computer and attempt to configure the LEDs using the mouse application running on the selected computer. Verify that the mouse programmable LEDs change state.
4. Disconnect the gaming mouse from the selected computer and connect it to the TOE mouse peripheral device port through the USB sniffer. Attempt to configure the LEDs using the mouse application running on the selected computer. Verify that the mouse programmable LEDs do not change state and that no traffic is sent and captured by the USB sniffer while the evaluator is not moving the mouse.
5. Connect a keyboard to the peripheral device interface through the USB sniffer. Use a keyboard emulation software application running on the selected computer to turn the keyboard Num Lock, Caps Lock, and Scroll Lock LEDs on and off. Verify that the LEDs on the keyboard do not change state and that no traffic is sent and captured by the USB sniffer.
6. Power down the TOE and disconnect the peripheral interface USB cable from the TOE to the selected computer and the peripheral devices from the TOE.
7. Power up the TOE and ensure the selected computer has not changed (this should have no effect on the selected computer because it was disconnected in the previous step). Reconnect the peripheral devices disconnected in step 6 to the TOE.
8. [If “mouse” is selected in FDP_PDC_EXT.3.1/KM, then] check that immediately following the connection, the mouse LEDs are illuminated (indicating that the peripheral devices are powered on, although the selected computer is not connected). [If “keyboard” is selected in FDP_PDC_EXT.3.1/KM, then] check that immediately following the connection, the Num Lock, Caps Lock, and Scroll Lock keyboard LEDs are blinking momentarily and then stay off (indicating that the keyboard is powered on, although the selected computer is not connected).
9. Turn the TOE off and disconnect the peripheral devices connected in step 6.
10. Reconnect the first computer interface USB cable to the TOE.
11. Turn on the TOE and check the computer real-time hardware information console for the presence of the peripheral devices connected in step 6 and disconnected in step 9. The presence of the TOE peripheral devices in the information console when the peripheral devices are not connected to the TOE indicates that the TOE emulates the KM devices.
12. [Conditional] If the TOE keyboard and mouse do not appear in the listed devices, repeat the following steps for both mouse and keyboard to simulate USB traffic:
 - Connect a USB generator to the TOE peripheral device interface port.
 - Configure the USB generator to enumerate as a generic HID mouse/keyboard device and then to generate a random stream of mouse/keyboard report packets.
 - Connect a USB sniffer device between the TOE computer interface and the USB port on the first computer to capture the USB traffic between the TOE and the first computer.
 - Turn on the TOE and verify that no packets cross the TOE following the device enumeration.This test step was not performed, since the keyboard and mouse correctly appeared in the listed devices in the device manager.

Unidirectional flow and isolation of USB traffic has been tested. The evaluator has confirmed that USB traffic is enforced properly and in a single direction.



Units Tested	AVS-4228, XDS441FX
Result	PASS

Test 4

This test is only applicable for the AVS-4228 and AVS-42216 models. The condition “Switching can be initiated only through express user action” in FDP_SWI_EXT.1.1 is selected for the AVS-4228 and AVS-42216 models. The condition “the TOE supports only one connected computer” in FDP_SWI_EXT.1.1 is selected for the XDS441 and XDS441FX models.

1. Ensure the TOE and the Operational Environment are configured in accordance with the operational guidance. Connect a display directly to each connected computer. Perform steps 2-10 for each connected computer.
2. Connect a USB sniffer between a non-selected TOE KM computer interface and its computer. Run USB protocol analyzer software on all remaining computers.
3. Turn on the TOE and observe the TOE enumeration data flow in the protocol analyzer connected to the selected computer and is not in any other USB protocol analyzers or the USB sniffer.
4. Ensure the TOE is switched to the first computer.
5. Reboot the first computer. Verify that no USB traffic is captured on all non-selected computer USB protocol analyzers.
6. Generate intensive USB HID traffic by moving the mouse at high speed and/or holding down the keyboard space key at the same time. Verify that no new USB traffic is captured on all non-selected computer USB protocol analyzers.
7. Perform steps 8 and 9 for each TOE keyboard/mouse peripheral interface.
8. Connect a USB dummy load into the TOE KM peripheral device interface. Verify that no new USB traffic is captured on all non-selected computer USB protocol analyzers. Remove the plug after the step is completed.
9. Connect a switchable 5-volt power supply with any compatible USB plug into the TOE KM peripheral device interface. Modulate the 5-volt supply (i.e., cycle on and off) manually at various speeds from approximately one cycle per five seconds to one cycle per second. Verify that no new USB traffic is captured on all non-selected computer USB analyzers.
10. Turn off the TOE. Verify that no new traffic is captured.

Correct data flow while the TOE is powered on or powered off has been tested. The evaluator confirmed that USB traffic is only captured on selected authorized computers.

Units Tested	AVS-4228
Result	PASS

Test 5

1. Configure the TOE and the Operational Environment in accordance with the operational guidance. Connect an authorized peripheral device for each peripheral device type selected in



FDP_PDC_EXT.3.1/KM. Connect two computers to a different display and run an instance of a text editor and USB analyzer software on each computer.

2. Connect the first computer to the TOE and ensure it is selected and that no other computers are connected.
3. Exercise the functions of the peripheral device type selected in FDP_PDC_EXT.3.1/KM and verify that the expected results are observed on the selected computer and that the expected traffic is sent and captured using the USB analyzer.
4. Disconnect the first computer. Generate intensive USB HID traffic by moving the mouse at high speed and/or holding down the keyboard space key at the same time.
5. Cease generation of the USB HID traffic, connect the second computer to the same port and ensure it is selected.
6. Verify that no results from the previous use of the peripheral device are observed on the selected computer and that no traffic is sent and captured using the USB analyzer.
7. Reboot the TOE and repeat step 6.
8. Turn off the TOE and repeat step 6.
9. Restart the TOE and repeat step 6.
10. Exercise the functions of the peripheral device type selected in FDP_PDC_EXT.3.1/KM and verify that the expected results are observed on the selected computer and that the expected traffic is sent and captured using the USB analyzer.

Data flow through the same interface has been observed and tested. The evaluator confirmed that the TOE does not send data to different computers connected to the same interface at different times.

Units Tested	AVS-4228, XDS441FX
Result	PASS

2.1.3 FDP_APC_EXT.1/VI Active PSD Connections

2.1.3.1 FDP_APC_EXT.1.1/VI

The TSF shall route user data only from the interfaces selected by the user.

Evaluation activities are detailed below.

2.1.3.2 FDP_APC_EXT.1.2/VI

The TSF shall ensure that no data or electrical signals flow between connected computers whether the TOE is powered on or powered off.

Evaluation activities are detailed below.

2.1.3.3 FDP_APC_EXT.1.3/VI

The TSF shall ensure that no data transits the TOE when the TOE is powered off.

Evaluation activities are detailed below.

2.1.3.4 FDP_APC_EXT.1.4/VI

The TSF shall ensure that no data transits the TOE when the TOE is in a failure state.



Application Note

This SFR is refined from the PSD PP for this PP-Module to include further restrictions for electrical signals. It is unlikely that this element can be satisfied unless video/display peripheral device interfaces are electrically and logically isolated from the connected computer interfaces or through other methods.

If the TOE claims conformance to multiple PP-Modules, each PP-Module modifies this SFR in a different manner for the interfaces that are unique to that module. In this case, the ST author should reference this modification of the SFR as "FDP_APC_EXT.1/VI" for uniqueness. Note that all elements of FDP_APC_EXT.1 must be included in this iteration, not just the ones that are modified by this PP-Module.

Evaluation Activity

Isolation Document

The evaluator shall examine the Isolation Document and verify it describes how the TOE ensures that no data or electrical signals flow between connected computers in both cases (powered on, powered off).

TSS

There are no guidance EAs for this component beyond what the PSD PP requires.

[Note to evaluator: This was copied directly from mod_vi_v1.0-sd.pdf. It is unclear whether NIAP intended no TSS EAs or whether the TSS EAs are missing.]

Guidance

There are no guidance EAs for this component beyond what the PSD PP requires.

Test

The evaluator shall perform the following tests:

Test 1-VI: Video Source Selection and Identification, TOE Off and Failure States

This test verifies the TOE switching function operates properly and will stop the video output display when in an OFF or FAILURE state.

Step 1: Configure the TOE and the Operational Environment in accordance with the operational guidance.

Step 2: Play a different video with embedded audio on a number of computers for each TOE computer video interface.

Step 3: Connect each computer to a TOE computer video interface.

Step 4: Connect a display to each TOE display interface.

Step 5: Turn on the TOE.

Step 6: For each connected computer, ensure it is selected and verify that the video and its accompanying audio from the selected computer(s) are received on the proper display(s).

*Step 7: [Conditional: if the TOE claims Combiner Use Case then] verify that video generated by the TOE has clear identification marking or text to properly identify the source computer shown. **Note: TD0539 applied***

Step 8: Turn off the TOE and verify that no video appears on any connected display.

Step 9: Power on the TOE and cause the TOE to enter a failure state. Verify that the TOE provides the user with a visual indication of failure and that no usable video appears on any connected display.

Step 10: Repeat steps 3 to 9 for each unique display protocol and port type supported by the TOE.

Test 2-VI: Computer Video Interface Isolation

[Conditional: perform this test if "switching can be initiated only through express user action" is selected in FDP_SWI_EXT.1.1 in the PSD PP.]

This test verifies that the TOE does not transfer data to any non-selected computer video interface.

Step 1: Configure the TOE and the Operational Environment in accordance with the operational guidance. Connect only the first



computer interface cable to one computer. Turn on the TOE.

Step 2: Switch the TOE primary display to computer #1.

Step 3: Observe the primary display to verify that the selected computer is the one that is shown.

Step 4: Remove the non-selected computer video interface cables from the TOE and connect the oscilloscope probe to the TOE #2 computer video interface to verify that no SYNC signal is passed through the TOE. Based on the connection interface protocol, this is performed as follows:

1. Video Graphics Array (VGA) – single ended probe on pins 13 and then 14;
2. High-Definition Multimedia Interface (HDMI) – connect pin 19 to a 3.3V power supply via a 100 Ohm resistor to provide Hot Plug Detect (HPD) signal; Check for signals - differential probe between pins 10 (+) and 12 (-);
3. Digital Visual Interface (DVI)-I – connect pin 16 to a 3.3V power supply via a 100 Ohm resistor to provide HPD signal; Check for signals - single ended probe on pins 8 and C4. Differential probe between pins 23 (+) and 24 (-);
4. DVI-D - connect pin 16 to a 3.3V power supply via a 100 Ohm resistor to provide HPD signal; Check for signals - Differential probe between pins 23 (+) and 24 (-);
5. DisplayPort - connect pin 18 to a 3.3V power supply via 100 Ohm resistor to provide HPD signal; Check for signals - Differential probe between pins 3 (-) and 1 (+) and between 10 (-) and 12 (+);
6. USB Type-C with DisplayPort as Alternate Function – connect pin A8 to a 3.3V power supply via a 100 Ohm resistor to provide HPD signal; Check for signals – Differential probe between pins A2 and A3, A10 and A11; B2 and B3, and B10 and B11.

Step 5: Repeat steps 3 and 4 while selecting other TOE connected computers. Verify that no SYNC signal is present.

Step 6: Repeat steps 3 to 5 with the TOE unpowered. Verify that no SYNC signal is present.

Step 7: With the probe connected to the TOE computer #2 video interface, disconnect / reconnect the computer #1 video cable. Power up the TOE and select computer #1. Attempt to detect the change in the oscilloscope at each one of the TOE #2 computer video interface pins. No changes shall be detected.

Step 8: Repeat step 7 for each one of the other TOE computer video interfaces.

Step 9: Repeat steps 7 and 8, but instead of disconnecting / reconnecting the computer, disconnect and reconnect the display.

Step 10: Repeat steps 7 and 8, but instead of disconnecting / reconnecting the computer, reboot the selected computer.

Step 11: Repeat steps 2 to 10 with each connected computer.

Step 12: [Conditional: if “multiple connected displays” is selected in FDP_CDS_EXT.1.1 then] repeat steps 3 to 10 with each other display connected to the TOE.

Step 13: Repeat this test for each unique display protocol and port type supported by the TOE.

Test 3-VI - Unauthorized Sub-protocols

Note that in the following steps only native video protocol cables shall be used. No conversion from other video protocols is allowed in these tests except as directed in FDP_IPC_EXT.1.1.

This test verifies that unauthorized sub-protocols are blocked.

Perform this test for each of the selections in FDP_PDC_EXT.3.1/VI and FDP_IPC_EXT.1.1.

In the following steps the evaluator shall establish a verified test setup that passes video signals across the TOE.

Step 1: Connect at least one computer with a native video protocol output to the TOE computer #1 video input interface.

Step 2: Connect at least one display with native video protocol to the TOE display output.

Step 3: Power up the TOE and ensure the connected computer is selected.

Step 4: Verify that the video image is visible and stable on the user display.

In the following steps the evaluator shall verify that the test setup properly blocks the unauthorized video sub-protocol traffic.



Step 5: Open the Monitor Control Command Set (MCCS) control console program on the computer and attempt to change the display contrast and brightness. Verify that the display does not change its contrast and brightness accordingly.

Step 6: Disconnect the video cable connecting the display and the TOE and connect the display directly to the computer. Verify that the video image is visible and stable on the user display. **Note: TD0514 applied**

Step 7: Attempt to change the display contrast and brightness. Verify that the display does change its contrast and brightness accordingly.

Step 8: Connect the following testing device based on the display video protocol being tested at the peripheral display interface:

1. DisplayPort – DisplayPort AUX channel analyzer in series between the display and the TOE
2. HDMI– HDMI sink test device
3. USB Type-C with DisplayPort as Alternate Function – USB sniffer in series between the display and the TOE
4. VGA – VGA sink test device
5. DVI-I/DVI-D – DVI sink test device

Note: TD0584 applied

Step 9: Attempt to change the display contrast and brightness. Verify that the testing device does not capture any MCCS commands.

Step 10: Replace the computer with a source generator for each selected protocol at the computer video interface. If DVI-I or DVI-D is selected, use an HDMI source generator.

Step 11: Run an EDID write transaction at the generator and verify in the testing device that no EDID traffic is captured.

Step 12: [Conditional, if DisplayPort, DVI-D, DVI-I, HDMI, or USB Type-C is the selected protocol being tested at the computer video interface, then] run Consumer Electronics Control (CEC) and High-bandwidth Digital Content Protection (HDCP) tests or commands at the generator and verify in the testing device that no CEC or HDCP traffic is captured.

Step 13: [Conditional, if DVI-D, DVI-I, or HDMI is the selected protocol being tested at the computer video interface, then] run Audio Return Channel (ARC), HDMI Ethernet and Audio Return Channel (HEAC), and HDMI Ethernet Channel (HEC) tests or commands at the generator and verify in the testing device that no ARC, HEAC, or HEC traffic is captured.

Step 14: [Conditional: If “[HDMI] protocol” is selected in FDP_IPC_EXT.1.2, then] perform steps 15 and 16 for both pin 13 (CEC) and 14 (UTILITY).

Step 15: Turn off the TOE. Use a multi-meter to measure the resistance-to-ground of the pin at the TOE HDMI peripheral interface and verify it is greater than 2 Mega-ohms.

Step 16: Attach a single ended oscilloscope probe between the pin and the ground, turn on the TOE, and verify that no changes between 0.0v and 0.2v and between 3.0v and 3.3v are detected.

Step 17: [Conditional: if VGA is not the selected protocol being tested, then] disconnect all devices. Connect the display to a TOE computer video interface and the oscilloscope to the TOE display interface in order to verify that no HPD signal is passed by measuring a signal voltage of less than 1.0V. Based on the selected protocol being tested, this is performed as follows:

1. HDMI – connect scope to pin 19 and verify no HPD signal is detected;
2. DVI-D/DVI-I – connect scope to pin 16 and verify no HPD signal is detected;
3. DisplayPort - connect scope to pin 18 and verify no HPD signal is detected;
4. USB Type-C with DisplayPort as Alternate Function – connect scope to pin A8 and B8 and verify no HPD signal is detected.

Step 18: Repeat this test for each of the selections in FDP_PDC_EXT.3.1/VI and FDP_IPC_EXT.1.2.

Test 4-VI - Video and EDID Channel Unidirectional Rule

This test verifies that the TOE video path is unidirectional from the computer video interface to the display interface with the exception of EDID, which may be read from the display once at power up and then may be read by the connected computers. The evaluator should have at least two high-resolution displays and one low-resolution display for each TOE-supported video protocol.

In the following steps the evaluator should attempt to read display EDID after the TOE completed its self-test / power up. The TOE



should not read the new display EDID.

Step 1: Configure the TOE and the Operational Environment in accordance with the operational guidance. Connect a computer and a high-resolution display to the TOE.

Step 2: Ensure the TOE is on, computer #1 is selected, and verify that the display shows video from computer #1 as expected.

Step 3: Turn off the TOE. Disconnect the user display from the TOE.

*Step 4: Connect the low-resolution display to the TOE and turn on the TOE. After the video is shown on the display, turn off the TOE and disconnect the low-resolution display. **Note: TD0506 applied***

*Step 5: Turn on the TOE. After the TOE has completed the self-test, connect the second high-resolution display of a different model to the TOE. the TOE may fail to generate video on the user display (i.e., no EDID is read at the TOE power up). If the display is showing video, then run the EDID reading and parsing software on computer #1 and check that there is no active EDID (i.e., the computer is using a default generic display or reading older display settings from the registry). **Note: TD0506 applied***

In the following steps the evaluator shall validate that the TOE video path is unidirectional from the computer video interface to the display interface.

Step 6: Perform steps 7-11 for each TOE computer video interface.

Step 7: Power off the TOE and disconnect the computer #1 video output and the display. Connect the display cable to the TOE computer #1 video interface. Connect the computer #1 video cable to the TOE display interface. This configuration will attempt to force video data through the TOE in the reverse direction.

Step 8: Power up the TOE again.

Step 9: Check that the video is not visible in the display.

Step 10: Perform steps 11 while the TOE is powered on and powered off.

Step 11: Remove the display cable from the TOE and connect the oscilloscope to verify that no SYNC signal is passed through the TOE. Based on the video protocols supported, this is performed as follows:

- 1. VGA – single ended probe on pins 13 and 14;*
- 2. HDMI – connect pin 19 to a 3.3V power supply via a 100 Ohm resistor to provide HPD signal; Check for signals - differential probe between pins 10 (+) and 12 (-);*
- 3. DVI-I – connect pin 16 to a 3.3V power supply via a 100 Ohm resistor to provide HPD signal; Check for signals - single ended probe on pins 8 and C4. Differential probe between pins 23 (+) and 24 (-);*
- 4. DVI-D - connect pin 16 to a 3.3V power supply via a 100 Ohm resistor to provide HPD signal; Check for signals - Differential probe between pins 23 (+) and 24 (-);*
- 5. DisplayPort - connect pin 18 to a 3.3V power supply via a 100 Ohm resistor to provide HPD signal; Check for signals - Differential probe between pins 3 (-) and 1 (+) and between 10 (-) and 12 (+);*
- 6. USB Type-C with DisplayPort as Alternate Function – connect pin A8 to a 3.3V power supply via a 100 Ohm resistor to provide HPD signal; Check for signals – Differential probe between pins A2 and A3, A10 and A11; B2 and B3, and B10 and B11.*

Test 5-VI – No Flow between Connected Computers over Time

This test verifies that the TOE does not send data to different computers connected to the same TOE video interface over time. Repeat this test for each TOE Video port.

Step 1: Configure the TOE and the Operational Environment in accordance with the operational guidance. Run EDID reading and parsing software on two computers and connect a display to the TOE.

Step 2: Connect computer #1 to the TOE, ensure the TOE is on, computer #1 is selected, no other computers are connected, and verify that the display shows video from computer #1 as expected.

Step 3: Capture the TOE EDID content in the software on computer #1 and save as a file with a name that indicates capture time.

Step 4: Disconnect computer #1 and connect an I2C programmer to the same port. Attempt to write the characters “FFFF” over the entire EDID address range.



Step 5: Disconnect the I2C programmer, reconnect computer #1 to the same port, and repeat step 3.

Step 6: Reboot the TOE and repeat step 3.

Step 7: Turn off the TOE and repeat step 3.

Step 8: Restart the TOE and repeat step 3.

Step 9: Disconnect computer #1 and repeat steps 2 to 8 with computer #2 on the same port.

Step 10: Repeat steps 2 to 9 for a total of 20 EDID file captures.

*Step 11: Collect all 20 captured EDID files, compare them bit-by-bit, and verify that they are identical excluding null captures recorded in Step 7. **Note: TD0584 applied***

Isolation Document Evaluator Assessment:

[Isol] Figure 1 illustrates all possible data flows for combiners and figure 2 shows all possible data flows for isolators. There follows Table 1 Data Flow Description for Combiners, that gives an explanation of all data flows for combiners and Table 2 Data Flow Description for Isolator Devices, which explains the data flows for isolators. Figures 1 and 2 which characterize the data flows various parts of the TOE (i.e. combiners, isolators) are part of the isolation justification and indicate the methods used to maintain the data separation. Section 2.3 of [Isol] gives an explanation of power isolation. Section 2.4 discusses programmable components. Section 3 describes the isolation enforcement policy for various aspects of the TOE. Figures 5, 7 and 8 show the policy enforcement and figure 6 shows the physical characteristics.

A complete analysis of the Isolation document is found in the file CFG_PSD-KM-VI - Annex D Adder Isolation Documentation assessment.doc.

TSS Evaluator Assessment:

Not applicable

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Test 1

1. Configure the TOE and the Operational Environment in accordance with the operational guidance.
2. Play a different video with embedded audio on a number of computers for each TOE computer video interface.
3. Connect each computer to a TOE computer video interface.
4. Connect a display to each TOE display interface.
5. Turn on the TOE.
6. For each connected computer, ensure it is selected and verify that the video and its accompanying audio from the selected computer(s) are received on the proper display(s).
7. *[Conditional: if the TOE claims the Combiner Use Case then]* verify that video generated by the TOE has clear identification marking or text to properly identify the source computer shown.
8. Turn off the TOE and verify that no video appears on any connected display.
9. Power on the TOE and cause the TOE to enter a failure state. Verify that the TOE provides the user with a visual indication of failure and that no usable video appears on any connected display.
10. Repeat steps 3 to 9 for each unique display protocol and port type supported by the TOE.

The evaluator confirmed that the TOE switching function operates properly and will stop the video output display when in an OFF or FAILURE state.



Units Tested	AVS-4228, XDS441FX
Result	PASS

Test 2

This test is only applicable for the AVS-4228 and AVS-42216 models. The condition “Switching can be initiated only through express user action” in FDP_SWI_EXT.1.1 is selected for the AVS-4228 and AVS-42216 models. The condition “the TOE supports only one connected computer” in FDP_SWI_EXT.1.1 is selected for the XDS441 and XDS441FX models.

1. Configure the TOE and the Operational Environment in accordance with the operational guidance. Connect only the first computer interface cable to one computer. Turn on the TOE.
2. Switch the TOE primary display to computer #1.
3. Observe the primary display to verify that the selected computer is the one that is shown.
4. Remove the non-selected computer video interface cables from the TOE and connect the oscilloscope probe to the TOE #2 computer video interface to verify that no SYNC signal is passed through the TOE. Based on the connection interface protocol, this is performed as follows:

Note: Video Graphics (VGA), DVI-D, DVI-I and USB Type-C with DisplayPort as Alternate Function are not supported by the TOE and as such were not tested.

High-Definition Multimedia Interface (HDMI) – connect pin 19 to a 3.3V power supply via a 100 Ohm resistor to provide Hot Plug Detect (HPD) signal; Check for signals - differential probe between pins 10 (+) and 12 (-);

DisplayPort - connect pin 18 to a 3.3V power supply via 100 Ohm resistor to provide HPD signal; Check for signals - Differential probe between pins 3 (-) and 1 (+) and between 10 (-) and 12 (+);

5. Repeat steps 3 and 4 while selecting other TOE connected computers. Verify that no SYNC signal is present.
6. Repeat steps 3 to 5 with the TOE unpowered. Verify that no SYNC signal is present.
7. With the probe connected to the TOE computer #2 video interface, disconnect / reconnect the computer #1 video cable. Power up the TOE and select computer #1. Attempt to detect the change in the oscilloscope at each one of the TOE #2 computer video interface pins. No changes shall be detected.
8. Repeat step 7 for each one of the other TOE computer video interfaces.
9. Repeat steps 7 and 8, but instead of disconnecting / reconnecting the computer, disconnect and reconnect the display.
10. Repeat steps 7 and 8, but instead of disconnecting / reconnecting the computer, reboot the selected computer.
11. Repeat steps 2 to 10 with each connected computer.
12. [Conditional: if “multiple connected displays” is selected in FDP_CDS_EXT.1.1 then] repeat steps 3 to 10 with each other display connected to the TOE.
13. Repeat this test for each unique display protocol and port type supported by the TOE.



The evaluator confirmed that the TOE does not transfer data to any non-selected computer video interface.

Units Tested	AVS-4228
Result	PASS

Test 3

1. Connect at least one computer with a native video protocol output to the TOE computer #1 video input interface.
2. Connect at least one display with native video protocol to the TOE display output.
3. Power up the TOE and ensure the connected computer is selected.
4. Power up the TOE and ensure the connected computer is selected.
5. Open the Monitor Control Command Set (MCCS) control console program on the computer and attempt to change the display contrast and brightness. Verify that the display does not change its contrast and brightness accordingly.
6. Disconnect the video cable connecting the display and the TOE and connect the display directly to the computer. Verify that the video image is visible and stable on the user display.
7. Attempt to change the display contrast and brightness. Verify that the display does change its contrast and brightness accordingly.
8. Connect the following testing device based on the display video protocol being tested at the peripheral display interface:

Note: Video Graphics (VGA), DVI-D/DVI-I and USB Type-C with DisplayPort as Alternate Function are not supported by the TOE and as such were not tested.

DisplayPort – DisplayPort AUX channel analyzer in series between the display and the TOE
HDMI – HDMI sink test device

9. Attempt to change the display contrast and brightness. Verify that the testing device does not capture any MCCS commands.
10. Replace the computer with a source generator for each selected protocol at the computer video interface.
11. Run an EDID write transaction at the generator and verify in the testing device that no EDID traffic is captured.
12. *For DisplayPort and HDMI* run Consumer Electronics Control (CEC) and High-bandwidth Digital Content Protection (HDCP) tests or commands at the generator and verify in the testing device that no CEC or HDCP traffic is captured.
13. *If HDMI is the selected protocol being tested at the computer video interface, then* run Audio Return Channel (ARC), HDMI Ethernet and Audio Return Channel (HEAC), and HDMI Ethernet Channel (HEC) tests or commands at the generator and verify in the testing device that no ARC, HEAC, or HEC traffic is captured.
14. *If “[HDMI] protocol” is selected in FDP_IPC_EXT.1.2, then* perform steps 15 and 16 for both pin 13 (CEC) and 14 (UTILITY).



15. Turn off the TOE. Use a multi-meter to measure the resistance-to-ground of the pin at the TOE HDMI peripheral interface and verify it is greater than 2 Mega-ohms.
16. Attach a single ended oscilloscope probe between the pin and the ground, turn on the TOE, and verify that no changes between 0.0v and 0.2v and between 3.0v and 3.3v are detected.
17. *[Conditional: if VGA is not the selected protocol being tested, then]* disconnect all devices. Connect the display to a TOE computer video interface and the oscilloscope to the TOE display interface in order to verify that no HPD signal is passed by measuring a signal voltage of less than 1.0V. Based on the selected protocol being tested, this is performed as follows:

Note: DVI-D/DVI-I and USB Type-C with DisplayPort as Alternate Function are not supported by the TOE and as such were not tested.

HDMI – connect scope to pin 19 and verify no HPD signal is detected;

DisplayPort - connect scope to pin 18 and verify no HPD signal is detected;

18. Repeat this test for each of the selections in FDP_PDC_EXT.3.1/VI and FDP_IPC_EXT.1.2

The evaluator has confirmed that the TOE successfully blocks unauthorized sub-protocols.

Units Tested	AVS-4228, XDS441FX
Result	PASS

Test 4

1. Configure the TOE and the Operational Environment in accordance with the operational guidance. Connect a computer and a high-resolution display to the TOE.
2. Ensure the TOE is on, computer #1 is selected, and verify that the display shows video from computer #1 as expected.
3. Turn off the TOE. Disconnect the user display from the TOE.
4. Connect the low-resolution display to the TOE and turn on the TOE. After the video is shown on the display, turn off the TOE and disconnect the low-resolution display.
5. Turn on the TOE. After the TOE has completed the self-test, connect the second high-resolution display of a different model to the TOE. The TOE may fail to generate video on the user display (i.e., no EDID is read at the TOE power up). If the display is showing video, then run the EDID reading and parsing software on computer #1 and check that there is no active EDID (i.e., the computer is using a default generic display or reading older display settings from the registry).
6. Perform steps 7-11 for each TOE computer video interface.
7. Power off the TOE and disconnect the computer #1 video output and the display. Connect the display cable to the TOE computer #1 video interface. Connect the computer #1 video cable to the TOE display interface. This configuration will attempt to force video data through the TOE in the reverse direction.
8. Power up the TOE again.
9. Check that the video is not visible in the display.
10. Perform steps 11 while the TOE is powered on and powered off.
11. Remove the display cable from the TOE and connect the oscilloscope to verify that no SYNC signal is passed through the TOE. Based on the video protocols supported, this is performed as follows:



Note: Video Graphics (VGA), DVI-D, DVI-I and USB Type-C with DisplayPort as Alternate Function are not supported by the TOE and as such were not tested.

HDMI – connect pin 19 to a 3.3V power supply via a 100 Ohm resistor to provide HPD signal; Check for signals - differential probe between pins 10 (+) and 12 (-);

DisplayPort - connect pin 18 to a 3.3V power supply via a 100 Ohm resistor to provide HPD signal; Check for signals - Differential probe between pins 3 (-) and 1 (+) and between 10 (-) and 12 (+);

The evaluator confirmed the TOE video path is unidirectional from the computer video interface to the display interface except for EDID.

Units Tested	AVS-4228, XDS441FX
Result	PASS

Test 5

1. Configure the TOE and the Operational Environment in accordance with the operational guidance. Run EDID reading and parsing software on two computers and connect a display to the TOE.
2. Connect computer #1 to the TOE, ensure the TOE is on, computer #1 is selected, no other computers are connected, and verify that the display shows video from computer #1 as expected.
3. Capture the TOE EDID content in the software on computer #1 and save as a file with a name that indicates capture time.
4. Disconnect computer #1 and connect an I2C programmer to the same port. Attempt to write the characters “FFFF” over the entire EDID address range.
5. Disconnect the I2C programmer, reconnect computer #1 to the same port, and repeat step 3.
6. Reboot the TOE and repeat step 3.
7. Turn off the TOE and repeat step 3.
8. Restart the TOE and repeat step 3.
9. Disconnect computer #1 and repeat steps 2 to 8 with computer #2 on the same port.
10. Repeat steps 2 to 9 for a total of 20 EDID file captures.
11. Collect all 20 captured EDID files, compare them bit-by-bit, and verify that they are identical excluding null captures recorded in Step 7.

The evaluator confirmed that that the TOE does not send data to different computers connected to the same TOE video interface over time.

Units Tested	AVS-4228, XDS441FX
Result	PASS

2.1.4 FDP_PDC_EXT.1 Peripheral Device Connection

Note: The inclusion of [MOD_VI_V1.0] triggers additions to the Peripheral Device Connections Policy (see Appendix E) associated with this SFR and additional Evaluation Activities.

2.1.4.1 FDP_PDC_EXT.1.1

The TSF shall reject connections with unauthorized devices upon TOE power up and upon connection of a peripheral device to a powered-on TOE.



Evaluation activities are detailed below.

2.1.4.2 FDP_PDC_EXT.1.2

The TSF shall reject connections with devices presenting unauthorized interface protocols upon TOE power up and upon connection of a peripheral device to a powered-on TOE.

Evaluation activities are detailed below.

2.1.4.3 FDP_PDC_EXT.1.3

The TOE shall have no external interfaces other than those claimed by the TSF.

Evaluation activities are detailed below.

2.1.4.4 FDP_PDC_EXT.1.4

The TOE shall not have wireless interfaces.

Evaluation activities are detailed below.

2.1.4.5 FDP_PDC_EXT.1.5

The TOE shall provide a visual or auditory indication to the User when a peripheral is rejected.

Application Note

The Peripheral Device Connections section is in Appendix E of both the PSD PP and this PP-Module. Keyboard and mouse peripheral device ports may be specific to only one type or interchangeable between them.

The TSF may elect to enforce rejection of unauthorized devices connected to the PSD through a USB hub by considering USB hubs as unauthorized devices, even though USB hubs are authorized devices. The TSF may elect to enforce rejection of unauthorized non-HID device classes of a composite device connected to a TOE KM peripheral interface by considering composite devices with non-HID device classes as unauthorized devices, even though the HID device classes are authorized.

[UA] The TSF may elect to enforce rejection of unauthorized devices connected to the PSD through a USB hub by considering USB hubs as unauthorized devices, even though USB hubs are authorized devices. If "internal" is the only selection made in FDP_PDC_EXT.4.1, then the TSF does not have to support USB as an authorized interface unless the KM PP-Module is also claimed by the ST author.

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this component.

TSS

The evaluator shall verify that the TSS describes the compatible devices for each peripheral port type supported by the TOE. The description must include sufficient detail to justify any PP-Modules that extend this PP and are claimed by the TOE (e.g., if the ST claims the Audio Input PP-Module, then the TSS shall reference one or more audio input devices as supported peripherals).

The evaluator shall verify that the TSS describes the interfaces between the PSD and computers and the PSD and peripherals, and ensure that the TOE does not contain wireless connections for these interfaces.

The evaluator shall verify that the list of peripheral devices and interfaces supported by the TOE does not include any prohibited peripheral devices or interface protocols specified in Appendix E.

The evaluator shall verify that the TSS describes all external physical interfaces implemented by the TOE, and that there are no external interfaces that are not claimed by the TSF.



Guidance

The evaluator shall verify that the operational user guidance provides clear direction for the connection of computers and peripheral devices to the TOE.

The evaluator shall verify that the operational user guidance provides clear direction for the usage and connection of TOE interfaces, including general information for computer, power, and peripheral devices.

The evaluator shall determine if interfaces that receive or transmit data to or from the TOE present a risk that these interfaces could be misused to import or export user data.

The evaluator shall verify that the operational user guidance describes the visual or auditory indications provided to a user when the TOE rejects the connection of a device.

[KM] The evaluator shall verify that the operational user guidance describes devices authorized for use with the TOE in accordance with the authorized peripheral device connections.

[UA] The evaluator shall verify that the operational user guidance describes devices authorized for use with the TOE in accordance with the authorized peripheral device connections.

[VI] The evaluator shall verify that the operational user guidance describes devices authorized for use with the TOE in accordance with the authorized peripheral device connections.

Test

Test 1: The evaluator shall check the TOE and its supplied cables and accessories to ensure that there are no external wired interfaces other than computer interfaces, peripheral device interfaces, and power interfaces.

Test 2: The evaluator shall check the TOE for radio frequency certification information to ensure that the TOE does not support wireless interfaces.

Test 3: The evaluator shall verify that the TOE ports properly reject unauthorized devices and devices with unauthorized protocols as per the Peripheral Device Connections (Appendix E).

For this test, verify device rejection through TOE user indication in accordance with the operational user guidance, an immediate cessation of traffic following device detection or enumeration, or incompatibility of the device interface with the peripheral interface, and through no such device appearing in the real-time hardware information console.

Step 1: Ensure the TOE is powered off. Open a real-time hardware information console on the connected computer.

Step 2: Attempt to connect a USB mass storage device to the TOE peripheral interface.

Step 3: Power on the TOE. Verify the device is rejected.

Step 4: Ensure the USB mass storage device is disconnected, and then attempt to connect it to the TOE peripheral interface again.

Step 5: Verify the device is rejected.

Step 6: Power off the TOE. Connect an unauthorized USB device to a USB hub, and attempt to connect the USB hub to the TOE peripheral interface.

Step 7: Power on the TOE. Verify the device is rejected.

Step 8: Ensure the USB hub is disconnected, and then attempt to connect it to the TOE peripheral interface again.

Step 9: Verify the device is rejected.

Step 10: Power off the TOE. Attempt to connect any Personal System/2 (PS/2) device directly to the TOE peripheral interface.

Step 11: Power on the TOE. Verify the device is rejected.

Step 12: Ensure the PS/2 device is disconnected, and then attempt to connect it directly to the TOE peripheral interface again.

Step 13: Verify the device is rejected.

Test 1-AO

The evaluator shall verify that the TOE ports properly reject unauthorized devices and devices with unauthorized protocols as per



the unauthorized peripheral device connections.

For this test, verify device rejection through TOE user indication in accordance with the operational user guidance or an immediate cessation of traffic following device detection or enumeration, or incompatibility of the device interface with the peripheral interface.

Step 1: Ensure the TOE is powered off and audio analyzer software is running on the connected computer.

Step 2: Connect an analog microphone to the TOE analog audio output peripheral interface.

Step 3: Power on the TOE, speak loudly into the microphone from approximately one-inch distance, and verify no audio is present in the audio analyzer software.

Step 4: Disconnect the microphone and reconnect it to the TOE peripheral interface.

Step 5: Speak loudly into the microphone from approximately one-inch distance, and verify no audio is present in the audio analyzer software.

Test 1-KM

The evaluator shall verify that the TOE ports properly reject unauthorized devices and devices with unauthorized protocols as per the unauthorized peripheral device connections.

For this test, verify device rejection through TOE user indication in accordance with the operational user guidance, an immediate cessation of traffic following device detection or enumeration, no traffic captured on the USB sniffer or analyzer software other than NAK transactions or system messages, or incompatibility of the device interface with the peripheral interface. Also verify device rejection through examination of the USB sniffer or analyzer software for no traffic captured other than NAK transactions or system messages and through examination of the real-time hardware console for no display of new USB devices (recognized or not recognized).

Repeat this test for each keyboard/mouse TOE peripheral interface.

Perform steps 1-6 for each of the following unauthorized devices:

- USB audio headset*
- USB camera*
- USB printer*
- USB user authentication device connected to a TOE keyboard/mouse peripheral interface*
- USB wireless LAN dongle*

Step 1: Ensure the TOE is powered off and connected to a computer. Run USB analyzer software on the connected computer and connect a USB sniffer to the TOE keyboard/mouse peripheral interface. Open the real-time hardware information console.

Step 2: Attempt to connect the unauthorized device to the USB sniffer.

Step 3: Power on the TOE. Verify the device is rejected.

Step 4: Ensure the unauthorized device is disconnected from the USB sniffer, then attempt to connect it to the USB sniffer again.

Step 5: Verify the device is rejected.

Step 6: Repeat steps 1 through 5 with a USB hub connected between the USB device and USB sniffer and observe that the results are identical.

Step 7: Repeat steps 1-6 with a composite device with non-HID device classes and verify that the non-HID functions are rejected or the entire device is rejected.

Test 2-KM

The evaluator shall verify that the TOE KM ports do not reject authorized devices and devices with authorized protocols as per the authorized peripheral device connections.

Repeat this test for each of the following four device types:

- Barcode reader;*



- Keyboard or Keypad;
- Mouse, Touchscreen, Trackpad, or Trackball; and
- PS/2 to USB adapter (with a connected PS/2 keyboard or mouse).

Step 1: Configure the TOE and the Operational Environment in accordance with the operational guidance. Run an instance of a text editor on a connected computer.

Step 2: Ensure the TOE is powered off.

Step 3: Connect the authorized device to the TOE peripheral interface.

Step 4: Power on the TOE. Verify the TOE user indication described in the operational user guidance is not present.

Step 5: Ensure the connected computer is selected and send inputs using the authorized devices. Verify that the input is received into the text editor or on the screen of the connected computer.

Step 6: Disconnect the authorized device, and then reconnect it to the TOE KM peripheral device interface.

Step 7: Verify the TOE user indication described in the operational user guidance is not present.

Step 8: Send inputs using the authorized devices. Verify that the input is received into the text editor or on the screen of the connected computer.

Test 1-VI

The evaluator shall verify that the TOE ports do not reject authorized devices and devices with authorized protocols as per the Peripheral Device Connections appendix in MOD_VI_V1.0.

Repeat this test for each of the selected protocols in FDP_PDC_EXT.3.1/VI:

Step 1: Connect the authorized device with an authorized protocol directly to a computer. Display any image on the device. Disconnect the device from the computer.

Step 2: Configure the TOE and the Operational Environment in accordance with the operational guidance.

Step 3: Ensure the TOE is powered off.

Step 4: Connect the authorized device with an authorized protocol to the TOE peripheral interface.

Step 5: Power on the TOE and verify the TOE user indication described in the operational user guidance is not present.

Step 6: Ensure the connected computer is selected and verify that the device displays the same image as in step 1.

Step 7: Disconnect the authorized device, then reconnect it to the TOE peripheral interface.

Step 8: Verify the TOE user indication described in the operational user guidance is not present.

Step 9: Verify that the device displays the same image as in step 1 and 6.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

[ST] TSS Section 9.1.1.4 states:

“The connected computers are attached to the TOE as follows:

- The TOE connects to the keyboard and mouse port using a USB A to USB B cable. The USB A end attaches to the computer, and the USB B end attaches to the TOE
- The TOE is connected to the computer video port using a video cable supporting DisplayPort or HDMI”

[ST] TSS Section 9.1.2.1 states “The TOE supports USB Type A HID's on keyboard and mouse ports.”



[ST] TSS Section 9.1.2.3 states “The TOE employs fixed device filtering and accepts only USB HID’s at the keyboard and mouse peripheral ports. Only USB Type A connections are permitted. The TOE does not support a wireless connection to a mouse, keyboard or USB hub.”

[ST] TSS Section 9.1.3 states “The TOE supports DisplayPort versions 1.1, 1.2 and 1.3, and HDMI 2.0”.

[ST] TSS Section 9.1.3.1 states:

“The AVS-42216, XDS441 and XDS441FX devices accept any DisplayPort or HDMI display device at the video peripheral ports. The AVS-4228 accepts any HDMI display device at the video peripheral ports. The TOE does not support a wireless connection to a video display.

The AVS-4228 and AVS-42216 devices support two video displays. The XDS441 and XDS441FX isolators support only one display.”

There are no wireless peripherals allowed in this configuration. The TSS section 9.1.2.3 of [ST] states “The TOE does not support a wireless connection to a mouse, keyboard or USB hub.”

The TSS describes all interfaces between the computers and the peripheral devices in section 9.1. The TOE is compliant to the PSD PP and does not allow non-compliant devices.

Guidance Evaluator Assessment:

The [QS-000040] and [QS-000047] contain detailed instructions on how to install the TOE with instructions for connection of supported computers.

Sections 4.4 and 4.5 of the [CC_Supp] describe the authorized peripherals for use with the TOE.

The evaluator has determined that the interfaces cannot be misused to import data.

Test Evaluator Assessment:

Test 1

1. Check the supplied cables and accessories to ensure there are no external wired interfaces other than the computer interfaces, peripheral device interfaces, and power interfaces.

The evaluator confirmed that all supplied cables and accessories contain no external wired interfaces. This excludes computer interfaces, peripheral device interfaces, and power interfaces.

Units Tested	AVS-4228, XDS441FX
Result	PASS

Test 2

1. Check the TOE for radio frequency certification information to ensure that the TOE does not support wireless interfaces.

The evaluator checked the TOE for radio frequency certification information and verified the TOE does not support wireless interfaces.

Units Tested	AVS-4228, XDS441FX
Result	PASS



Test 3

1. Ensure the TOE is powered off. Open a real-time hardware information console on the connected computer.
2. Attempt to connect a USB mass storage device to the TOE peripheral interface.
3. Power on the TOE. Verify the device is rejected.
4. Ensure the USB mass storage device is disconnected, and then attempt to connect it to the TOE peripheral interface again.
5. Verify the device is rejected.
6. Power off the TOE. Connect an unauthorized USB device to a USB hub, and attempt to connect the USB hub to the TOE peripheral interface.
7. Power on the TOE. Verify the device is rejected.
8. Ensure the USB hub is disconnected, and then attempt to connect it to the TOE peripheral interface again.
9. Verify the device is rejected.
10. Power off the TOE. Attempt to connect any Personal System/2 (PS/2) device directly to the TOE peripheral interface.
11. Power on the TOE. Verify the device is rejected.
12. Ensure the PS/2 device is disconnected, and then attempt to connect it directly to the TOE peripheral interface again.
13. Verify the device is rejected.

The evaluator confirmed that the TOE ports properly reject unauthorized devices and devices with unauthorized protocols as per the Peripheral Device Connections (Appendix E)

Units Tested	AVS-4228, XDS441FX
Result	PASS

2.1.5 FDP_PDC_EXT.2/KM Authorized Devices (Keyboard/Mouse)

2.1.5.1 FDP_PDC_EXT.2.1/KM

The TSF shall allow connections with authorized devices and functions as defined in [Appendix E] and [selection:

- *authorized devices as defined in the PP-Module for Audio Output Devices,*
- *authorized devices as defined in the PP-Module for User Authentication Devices,*
- *authorized devices as defined in the PP-Module for Video/Display Devices,*
- *no other devices*

] upon TOE power up and upon connection of a peripheral device to a powered-on TOE.

2.1.5.2 FDP_PDC_EXT.2.2/KM

The TSF shall allow connections with authorized devices presenting authorized interface protocols as defined in [Appendix E] and [selection:

- *authorized devices presenting authorized interface protocols as defined in the PP-Module for Audio Output Devices,*



- authorized devices presenting authorized interface protocols as defined in the PP-Module for User Authentication Devices,
- authorized devices presenting authorized interface protocols as defined in the PP-Module for Video/Display Devices,
- no other devices

] upon TOE power up and upon connection of a peripheral device to a powered-on TOE.

Application Note

The TSF must claim conformance to a PP-Configuration that includes each PP-Module contained in any selections. The ST author should select all devices and interfaces supported by the TOE.

If "authorized devices presenting authorized interface protocols as defined in the PP-Module for Video/Display Devices" is selected and "USB Type-C with DisplayPort as alternate function" is selected in FDP_PDC_EXT.3.1/Vid, then touch screen devices may not be used in conjunction with video devices that use USB Type-C with DisplayPort as alternate function.

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this SFR.

TSS

TSS evaluation activities for this SFR are performed under FDP_PDC_EXT.1 above.

Guidance

Guidance evaluation activities for this SFR are performed under FDP_PDC_EXT.1 above.

Test

Testing of this component is performed through evaluation of FDP_PDC_EXT.1 Test 2 as specified in [MOD_KM] section 2.1.4 above.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Not applicable

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Not applicable

2.1.6 FDP_PDC_EXT.3/KM Authorized Connection Protocols (Keyboard/Mouse)

2.1.6.1 FDP_PDC_EXT.3.1/KM

The TSF shall have interfaces for the [selection: USB (keyboard), USB (mouse)] protocols.

2.1.6.2 FDP_PDC_EXT.3.2/KM

The TSF shall apply the following rules to the supported protocols: [the TSF shall emulate any keyboard or mouse device functions from the TOE to the connected computer].

Application Note



It is expected that the ST author will make all selections in FDP_PDC_EXT.3.1/KM for which the TOE has an interface; the TOE boundary should encompass the entire device where possible.

If the TOE supports multiple connected computers (as specified by selecting "switching can be initiated only through express user action" in FDP_SWI_EXT.1.1 in the PSD PP), selections made in FDP_PDC_EXT.3.1 determine whether selection-based SFRs in Appendix B must be claimed. Specifically, selecting "USB (keyboard)" requires the TOE to claim FDP_RIP.1/KM and selecting both "USB (keyboard)" and "USB (mouse)" requires the TOE to claim FDP_SWI_EXT.3.

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this SFR.

TSS

The evaluator shall examine the TSS and verify it describes which types of peripheral devices that the PSD supports.

The evaluator shall examine the TSS to verify that keyboard or mouse device functions are emulated from the TOE to the connected computer.

Guidance

There are no guidance EAs for this component.

Test

Test activities for this SFR are covered under FDP_APC_EXT.1 tests 1-KM and 3-KM.

Evaluator Assessment

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

The TSS describes which peripherals are used in sections 9.1.2.2 states Device emulators are USB enabled microcontrollers that are programmed to emulate a standard USB keyboard and mouse composite device." Section 9.1.2.3 states "The TOE employs fixed device filtering and accepts only USB HIDs at the keyboard and mouse peripheral ports. Only USB Type A connections are permitted." Section 9.1.2.1 states "The TOE supports USB Type A HIDs on keyboard and mouse ports. The USB bidirectional communication protocol is converted into a unidirectional proprietary protocol, and is then converted back into the USB bidirectional protocol to communicate with the coupled computer hosts."

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Not applicable

2.1.7 FDP_PDC_EXT.2/VI Peripheral Device Connection (Video Output)

2.1.7.1 FDP_PDC_EXT.2.1/VI

The TSF shall allow connections with authorized devices as defined in [Appendix E] and [selection:

- authorized devices as defined in the PP-Module for Audio Output Devices,

- authorized devices and functions as defined in the PP-Module for Keyboard/Mouse Devices,



- authorized devices as defined in the PP-Module for User Authentication Devices,
- no other devices

] upon TOE power up and upon connection of a peripheral device to a powered-on TOE.

2.1.7.2 FDP_PDC_EXT.2.2/VI

The TSF shall allow connections with authorized devices presenting authorized interface protocols as defined in [Appendix E] and [selection:

- authorized devices presenting authorized interface protocols as defined in the PP-Module for Audio Output Devices,
- authorized devices presenting authorized interface protocols as defined in the PP-Module for Keyboard/Mouse Devices,
- authorized devices presenting authorized interface protocols as defined in the PP-Module for User Authentication Devices,
- no other devices

] upon TOE power up and upon connection of a peripheral device to a powered-on TOE.

Application Note

The TSF must claim conformance to a PP-Configuration that includes each PP-Module contained in any selections. The ST author should select all devices and interfaces supported by the TOE.

If "authorized devices presenting authorized interface protocols as defined in the PP-Module for Keyboard/Mouse" is selected and "USB Type-C with DisplayPort as alternate function" is selected in FDP_PDC_EXT.3.1/VI, then video devices that use USB Type-C with DisplayPort as alternate function may not be used in conjunction with touch screen devices.

Evaluation Activity

Isolation Document

There are no Isolation Document EAs for this component.

TSS

TSS evaluation activities for this SFR are performed under FDP_PDC_EXT.1 above.

Guidance

Guidance evaluation activities for this SFR are performed under FDP_PDC_EXT.1 above.

Test

Testing of this component is performed through evaluation of FDP_PDC_EXT.1 as specified in section 2.1.4 above.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Not applicable

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Not applicable



2.1.8 FDP_PDC_EXT.3/VI Authorized Connection Protocols (Video Output)

2.1.8.1 FDP_PDC_EXT.3.1/VI

The TSF shall have interfaces for the [selection: VGA, DVI-D, DVI-I, HDMI, DisplayPort, USB Type-C with DisplayPort as alternate function] protocols.

2.1.8.2 FDP_PDC_EXT.3.2/VI

The TSF shall apply the following rules to the supported protocols: [the TSF shall read the connected display EDID information once during power-on or reboot [selection: automatically, when prompted by user intervention]]. **Note: TD0620 applied.**

Application Note

It is expected that the ST author will make all selections in FDP_PDC_EXT.3.1/VI for which the TOE has an interface; the TOE boundary should encompass the entire device where possible.

If the KM PP-Module is also claimed by the ST, "USB Type-C with DisplayPort as alternate function" may not be selected in conjunction with a touchscreen peripheral device.

If "DisplayPort" is selected, the ST must include the selection-based requirement FDP_IPC_EXT.1.

This PP-Module defines several iterations of FDP_SPR_EXT.1. Depending on the selections made in FDP_PDC_EXT.3.1/VI, the evaluator must include the relevant iterations.

If the TOE can read the connected display EDID information during power-on or reboot without human intervention, the first selection item for FDP_PDC_EXT.3.2/VI is selected. If the TOE requires human intervention to read the connected display EDID during power-on or reboot, the second selection item is selected. **Note: TD0620 applied**

Evaluation Activity

Isolation Document

There are no Isolation Document EAs for this component.

TSS

TSS evaluation activities for this SFR are performed under FDP_PDC_EXT.1 above.

Guidance

Guidance evaluation activities for this SFR are performed under FDP_PDC_EXT.1 above.

Test

Testing of this component is performed through evaluation of FDP_APC_EXT.1 as specified in section 2.1.3 above.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Not applicable

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Not applicable



2.1.1.9 FDP_SWI_EXT.1 PSD Switching

2.1.1.9.1 FDP_SWI_EXT.1.1

The TSF shall ensure that [selection: the TOE supports only one connected computer, switching can be initiated only through express user action].

Application Note

If “switching can be initiated only through express user action” is selected, the ST must include the selection-based requirements FDP_SWI_EXT.2 and FTA_CIN_EXT.1.

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this component.

TSS

If the ST includes the selection the “TOE supports only one connected computer”, the evaluator shall verify that the TSS indicates that the TOE supports only one connected computer.

If the ST includes the selection “switching can be initiated only through express user action”, the evaluator shall verify that the TSS describes the TOE supported switching mechanisms and that those mechanisms can be initiated only through express user action.

Guidance

If the ST includes the selection “switching can be initiated only through express user action”, the evaluator shall verify that the operational user guidance describes the TOE supported switching mechanisms.

Test

There are no test Evaluation Activities for this component.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.1.1.1 of the [ST] states:

“The user determines the host computer to be connected to the peripherals by pressing a button on the TOE front panel, or on the remote control. The front panel button of the selected computer is illuminated. When the remote control is used, both the front panel button and the remote-control channel indicator for the selected computer are illuminated. These are always consistent. Switching can only be initiated through express user action.

Additionally, TOE devices may be switched with peripheral devices using a guard. This is done by moving the mouse to the edge of the screen while pressing the left CTRL key. “

Section 9.1.1.2 of the [ST] states, “The Adder XDS441 and XDS441FX devices support only one connected computer.”

Guidance Evaluator Assessment:

The [QS-000040] guide in the “Switching between computers” section explains the device switching mechanisms. [CC_Supp] section 4.6 explains the use of a guard.

Test Evaluator Assessment:

Not applicable



2.1.1.10 FDP_RIP_EXT.1 Residual Information Protection

2.1.10.1 FDP_RIP_EXT.1.1

The TSF shall ensure that no user data is written to TOE non-volatile memory or storage.

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this component.

TSS

The evaluator shall verify that the TSS includes a Letter of Volatility that provides the following information:

- Which TOE components have non-volatile memory, the non-volatile memory technology, manufacturer/part number, and memory sizes;*
- Any data and data types that the TOE may store on each one of these components;*
- Whether or not each one of these parts is used to store user data and how this data may remain in the TOE after power down; and*
- Whether the specific component may be independently powered by something other than the TOE (e.g., by a connected computer).*

Note that user configuration and TOE settings are not considered user data for purposes of this requirement.

The evaluator shall verify that the Letter of Volatility provides assurance that user data is not stored in TOE non-volatile memory or storage.

Guidance

There are no guidance Evaluation Activities for this component.

Test

There are no test Evaluation Activities for this component.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

The Letter of Volatility is provided as an annex, Annex A in the [ST]. It lists each component and explains which have volatile or non-volatile memory. It also states whether data is retained or not. The power source for each component is listed.

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Not applicable

2.1.1.11 FDP_UDF_EXT.1/KM Unidirectional Data Flow (Keyboard/Mouse)

2.1.11.1 FDP_UDF_EXT.1.1/KM

The TSF shall ensure [selection: keyboard, mouse] data transits the TOE unidirectionally from the [TOE [selection: keyboard, mouse]] peripheral interface(s) to the [TOE [selection: keyboard, mouse]] interface.

Application Note



Caps Lock, Num Lock, and Scroll Lock indications may be displayed by the TOE while still not passing that information to the keyboard.

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this SFR.

TSS

The evaluator shall examine the TSS to verify that it describes if and how keyboard Caps Lock, Num Lock, and Scroll Lock indications are displayed by the TOE and to verify that keyboard internal LEDs are not changed by a connected computer.

The evaluator shall examine the TSS to verify that keyboard and mouse functions are unidirectional from the TOE keyboard/mouse peripheral interface to the TOE keyboard/mouse computer interface.

Guidance

There are no guidance EAs for this component.

Test

Test activities for this SFR are covered under FDP_APC_EXT.1 test 3-KM.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.1.2.1 of the [ST] explains how the flows to the keyboard/mouse are unidirectional. “The TOE uses optical data diodes to enforce a unidirectional data flow from the user peripherals to the coupled hosts and uses isolated device emulators to prevent data leakage through the peripheral switching circuitry.”

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Not applicable

2.1.12 FDP_UDF_EXT.1/VI Unidirectional Data Flow (Video Output)

2.1.12.1 FDP_UDF_EXT.1.1/VI

The TSF shall ensure [video] data transits the TOE unidirectionally from the [TOE computer video] interface to the [TOE peripheral device display] interface.

Evaluation Activity

Isolation Document

There are no Isolation Document EAs for this component.

TSS

There are no TSS EAs for this component.

Guidance

There are no guidance EAs for this component.

Test



This component is evaluated through evaluation of FDP_APC_EXT.1 as specified in section 2.1.3 above.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Not applicable

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Not applicable

2.2 Protection of the TSF (FPT)

2.2.1 FPT_FLS_EXT.1 Failure with Preservation of Secure State

2.2.1.1 FPT_FLS_EXT.1.1

The TSF shall preserve a secure state when the following types of failures occur: failure of the power-on self-test and [selection: failure of the anti-tamper function, no other failures]

Application Note

In the context of this PP, a 'secure state' is defined by the TOE disabling all peripheral and connected computer interfaces when the correctness of its own functions cannot be assured.

Failure of the anti-tamper function should be selected if FPT_PHP.3 is included in the ST.

Evaluation Activity

This SFR is evaluated in conjunction with FPT_TST.1.

Evaluator Assessment:

NA Tested with FPT_TST.1

2.2.2 FPT_NTA_EXT.1 PSD No Access to TOE

2.2.2.1 FPT_NTA_EXT.1.1

TOE firmware, software, and memory shall not be accessible via the TOE's external ports, with the following exceptions: [selection: the Extended Display Identification Data (EDID) memory of Video TOEs may be accessible from connected computers; the configuration data, settings, and logging data that may be accessible by authorized administrators; no other exceptions].

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this component.

TSS

The evaluator shall examine the TSS to ensure that the TSS documents that connected computers and peripherals do not have access to TOE software, firmware, and TOE memory, except as described above.

**Guidance**

The evaluator shall check the operational user guidance to ensure any configurations required to comply with this SFR are defined.

Test

There are no test Evaluation Activities for this component.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.2.1 of [ST] states:

“Connected computers do not have access to TOE firmware or memory, with the exception of EDID data, which is accessible from the TOE to connected computers.

TOE microcontrollers run from internal protected flash memory. Firmware cannot be updated from an external source.”

Guidance Evaluator Assessment:

The [QS-000040], [QS-000045] and [QS-000047] have a warning that tamper evident seals are being used on the device.

Test Evaluator Assessment:

Not applicable

2.2.3 FPT_PHP.1 Passive Detection of Physical Attack**2.2.3.1 FPT_PHP_1.1**

The TSF shall provide unambiguous detection of physical tampering that might compromise the TSF.

2.2.3.2 FPT_PHP_1.2

The TSF shall provide the capability to determine whether physical tampering with the TSF's devices or TSF's elements has occurred.

Application Note

FPT_PHP.1.1 include indications generated from application of optional SFR FPT_PHP.3

Evaluation Activity**Isolation Document**

There are no Isolation Document evaluation activities for this component.

TSS

The evaluator shall verify that the TSS indicates that the TOE provides unambiguous detection of physical tampering of the TOE enclosure and TOE remote controller (if applicable). The evaluator shall verify that the TSS provides information that describes how the TOE indicates that it has been tampered with.

Guidance

The evaluator shall verify that the operational user guidance describes the mechanism by which the TOE provides unambiguous detection of physical tampering and provides the user with instructions for verifying that the TOE has not been tampered with.

Test

Test 1: The evaluator shall verify, for each tamper evident seal or label affixed to the TOE enclosure and TOE remote controller (if



applicable), that any attempts to open the enclosure or remove the seal results in the seal being damaged in a manner that is consistent with the operational user guidance.

Test 2: The evaluator shall verify that it is not possible to administratively disable or otherwise prevent the display of any tampering indicators.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.2.2 of [ST] explains the anti-tamper mechanisms, the tamper evident seals. If a seal is removed, the word VOID appears to indicate the TOE has been tampered.

Guidance Evaluator Assessment:

The [QS-000040] and [QS-000047] section “Notes and warnings” mentions, “Holographic anti-tampering labels protect the product’s enclosure, providing a clear visual indication if it has been opened or compromised.”

Test Evaluator Assessment:

Test 1

1. Removed the tamper evident seals from the TOE.

The evaluator confirmed that any attempt to open the enclosure or remove the seal results in the seal being damaged in a manner that is consistent with the operational user guidance.

Units Tested	AVS-4228, XDS441FX
Result	PASS

Test 2

1. Attempt to remove the tamper evident seals from the TOE without damaging the tampering indicators.

The evaluator confirmed that it is not possible to administratively disable or otherwise prevent the display of any tampering indicators.

Units Tested	AVS-4228, XDS441FX
Result	PASS

2.2.4 FPT_TST.1 TSF Testing

2.2.4.1 FPT_TST.1.1

The TSF shall run a suite of self-tests [during initial start-up and at the conditions [selection: upon reset button activation, no other conditions]] to demonstrate the correct operation of [user control functions and [selection: active anti-tamper functionality, no other functions]].



2.2.4.2 FPT_TST.1.2

The TSF shall provide authorized users with the capability to verify the integrity of [selection: [assignment: parts of TSF data], TSF data].

2.2.4.3 FPT_TST.1.3

The TSF shall provide authorized users with the capability to verify the integrity of [selection: [assignment: parts of TSF], TSF].

Application Note

Reset button activation should be selected if the TOE includes such functionality.

If "active anti-tamper functionality" is selected, portions of the evaluation activities will test functions from the optional active anti-tamper SFR FPT_PHP.3.

Anyone with physical access to the TOE can be considered an authorized user.

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this component.

TSS

The evaluator shall verify that the TSS describes the self-tests that are performed on start up or on reset (if "upon reset button activation" is selected). The evaluator shall verify that the self-tests cover at least the following:

- a) a test of the user interface – in particular, tests of the user control mechanism (e.g., checking that the front panel push-buttons are not jammed); and
- b) if "active anti-tamper functionality" is selected, a test of any antitampering mechanism (e.g., checking that the backup battery is functional).

The evaluator shall verify that the TSS describes how the TOE ensures a shutdown upon a self-test failure or a failed anti-tampering function, if present. If there are instances when a shutdown does not occur (e.g., a failure is deemed non-security relevant), those cases are identified and a rationale is provided explaining why the TOE's ability to enforce its security policies is not affected.

The evaluator shall check the TSS to verify that it describes the TOE behavior in case of self-test failure. The evaluator shall verify that the described TOE behavior includes shutting down the PSD functionality once the failure is detected.

The evaluator shall examine the TSS to verify that it describes how users verify the integrity of the selections in FPT_TST.1.2 and FPT_TST.1.3. This method can include restarting the TOE, a dedicated self-test, or some other method.

Guidance

The evaluators shall verify that the operational user guidance describes how users verify the integrity of the selections in FPT_TST.1.2 and FPT_TST.1.3. This method can include restarting the TOE, a dedicated self-test, or some other method.

Test

The evaluator shall trigger the conditions specified in the TSS that are used to initiate TSF self-testing and verify that successful completion of the self-tests can be determined by following the corresponding steps in the operational guidance.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.2.3 of the [ST] discusses the self-test and what it encompasses:

"The TOE performs a self-test at initial start-up. The self-test runs independently on the microcontroller and performs verification of the integrity of the microcontroller firmware. On the AVS-



4228 and AVS-42216 devices, the self-test also performs the following checks:

- Verification of the front panel push-buttons
- Verification of computer port isolation. This is tested by sending test packets to various interfaces and attempting to detect this traffic at all other interfaces

if the self-test fails, the LEDs on the device blink to indicate the failure. The AVS-4228 and AVS-42216 devices also make a clicking sound. The TOE disables the data flow functionality and remains in a disabled state until the self-test is rerun and passes.”

Guidance Evaluator Assessment:

The [QS-00040] states “When the unit powers up it performs a self-test procedure. If the self-test fails for any reason, including a jammed button, the unit will become inoperable. The front panel indicators will show an abnormal display. Contact technical support and avoid using the product.”

Section 4.1 of the [CC_Supp] describes the self-test and failure behavior and advises to contact Adder Technical Support if rebooting does not clear the failure.

Test Evaluator Assessment:

Test 1 (a)

1. The TOE must be powered off, ensure the power cable is removed from the TOE before proceeding.
2. Remove all HID devices and power on combiner device. This will cause the unit to enter a self-test failure mode where the TOE will be powered on, but unusable.
3. The evaluator ensured no video/keyboard/mouse is being output from the TOE while it is in self-test failure state.

The evaluator confirmed that that successful completion of the self-tests can be determined by following the corresponding steps in operational guidance.

Units Tested	AVS-4228
Result	PASS

Test 1 (b)

1. The TOE must be powered off, ensure the power cable is removed from the TOE before proceeding.
2. Disconnect the display for at least five seconds and power on the unit. This will cause the unit to enter a self-test failure mode where the TOE will be powered on, but unusable.
3. The evaluator ensured no video/keyboard/mouse is being output from the TOE while it is in self-test failure state.

The evaluator confirmed that that successful completion of the self-tests can be determined by following the corresponding steps in operational guidance.

Units Tested	XDS441FX
Result	PASS



2.2.5 FPT_TST_EXT.1 TSF Testing

2.2.5.1 FPT_TST_EXT.1.1

The TSF shall respond to a self-test failure by providing users with a [selection: visual, auditory] indication of failure and by shutdown of normal TSF functions.

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this component.

TSS

The evaluator shall check the TSS to verify that it describes the TOE behavior in case of self-test failure. The evaluator shall verify that the described TOE behavior includes shutting down the PSD functionality once the failure is detected.

Guidance

The evaluator shall verify that the operational user guidance:

- a) describes how the results of self-tests are indicated to the user*
- b) provides the user with a clear indication of how to recognize a failed self test; and*
- c) details the appropriate actions to be completed in the event of a failed self-test.*

The evaluator shall verify that the operational user guidance provides adequate information on TOE self-test failures, their causes, and their indications.

Test

The evaluator shall cause a TOE self-test failure and verify that the TOE responds by disabling normal functions and provides proper indications to the user.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.2.3 of [ST] states that if the self-test fails the front panel LEDs blink and the AVS-4228 and AVS-42216 devices make a clicking sound. The TOE disables the PSD switching functionality and remains in a disabled state until the self-test is rerun and passes.

Guidance Evaluator Assessment:

The [QS-00040] states “When the unit powers up it performs a self-test procedure. If the self-test fails for any reason, including a jammed button, the unit will become inoperable. The front panel indicators will show an abnormal display. Contact technical support and avoid using the product.”

Section 4.1 of the [CC_Supp] describe the self-test and failure behavior and advises to contact Adder Technical Support if rebooting does not clear the failure.

Test Evaluator Assessment:

Test 1 (a)

1. The TOE must be powered off, ensure the power cable is removed from the TOE before proceeding.
2. Remove all HID devices and power on combiner device. This will cause the unit to enter a self-test failure mode where the TOE will be powered on, but unusable.



3. The evaluator ensured no video/keyboard/mouse is being output from the TOE while it is in self-test failure state.

The evaluator confirmed that the TOE does perform a self-test failure and that the TOE responds by disabling normal functions and provides proper indications to the user.

Units Tested	AVS-4228
Result	PASS

Test 1 (b)

1. The TOE must be powered off, ensure the power cable is removed from the TOE before proceeding.
2. Disconnect the display for at least five seconds and power on the unit. This will cause the unit to enter a self-test failure mode where the TOE will be powered on, but unusable.
3. The evaluator ensured no video/keyboard/mouse is being output from the TOE while it is in self-test failure state.

The evaluator confirmed that that successful completion of the self-tests can be determined by following the corresponding steps in operational guidance.

Units Tested	XDS441FX
Result	PASS

3 Evaluation Activities for Optional Requirements

3.1 User Data Protection (FDP)

3.1.1 FDP_FIL_EXT.1/KM Device Filtering (Keyboard/Mouse)

3.1.1.1 FDP_FIL_EXT.1.1/KM

The TSF shall have [selection: configurable, fixed] device filtering for [selection: keyboard, mouse] interfaces.

3.1.1.2 FDP_FIL_EXT.1.2/KM

The TSF shall consider all [PSD KM] blacklisted devices as unauthorized devices for [selection: keyboard, mouse] interfaces in peripheral device connections.

3.1.1.3 FDP_FIL_EXT.1.3/KM

The TSF shall consider all [PSD KM] whitelisted devices as authorized devices for [selection: keyboard, mouse] interfaces in peripheral device connections only if they are not on the [PSD KM] blacklist or otherwise unauthorized.

Application Note

The ST author must make the selections for the device which the TOE has: configurable or fixed or both; and keyboard or mouse or both.

Evaluation Activity

Isolation Document



There are no Isolation Document evaluation activities for this SFR.

TSS

The evaluator shall examine the TSS and verify that it describes whether the PSD has configurable or fixed device filtering.

[Conditional - If "configurable" is selected in FDP_FIL_EXT.1.1/KM, then:] the evaluator shall examine the TSS and verify that it describes the process of configuring the TOE for whitelisting and blacklisting KM peripheral devices, including information on how this function is restricted to administrators. The evaluator shall verify that the TSS does not allow TOE device filtering configurations that permit unauthorized devices on KM interfaces.

Guidance

[Conditional - If "configurable" is selected in FDP_FIL_EXT.1.1/KM, then:] the evaluator shall examine the guidance documentation and verify that it describes the process of configuring the TOE for whitelisting and blacklisting KM peripheral devices and the administrative privileges required to do this.

Test

Test 1

Perform the test steps in FDP_PDC_EXT.1 with all devices on the PSD KM blacklist and verify that they are rejected as expected.

Test 2

[Conditional: Perform this only if "configurable" is selected in FDP_FIL_EXT.1.1/KM]

In the following steps the evaluator shall verify that whitelisted and blacklisted devices are treated correctly.

Step 1: Ensure the TOE and the Operational Environment are configured in accordance with the operational guidance.

Step 2: Connect to the TOE KM peripheral device interface a composite device which contains a HID class and a non-HID class.

Step 3: Configure the TOE KM CDF to whitelist the composite device.

Step 4: Verify that the HID-class part is accepted and that the non-HID class part is rejected through real-time device console and USB sniffer capture, or that the entire device is rejected.

Step 5: Configure the TOE KM CDF to blacklist the device.

Step 6: Verify that both the HID-class part and the non-HID class part is rejected through real-time device console and USB sniffer capture.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

NA - The selection is fixed – blacklisted devices are unauthorized and whitelisted devices are authorized. [ST] TSS Section 9.1.2.3 states “The TOE employs fixed device filtering and accepts only USB HIDs at the keyboard and mouse peripheral ports. Only USB Type A connections are permitted. The TOE does not support a wireless connection to a mouse, keyboard or USB hub.”

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Test 1

1. Ensure the TOE is powered off and connected to a computer. Run USB analyzer software on the connected computer and connect a USB sniffer to the TOE keyboard/mouse peripheral interface. Open the real-time hardware information console.



2. Attempt to connect the unauthorized device to the USB sniffer:
 - USB audio headset
 - USB camera
 - USB printer
 - USB user authentication device connected to a TOE keyboard/mouse peripheral interface
 - USB wireless LAN dongle
3. Power on the TOE. Verify the device is rejected.
4. Ensure the unauthorized device is disconnected from the USB sniffer, then attempt to connect it to the USB sniffer again.
5. Verify the device is rejected.
6. Repeat steps 1 through 5 with a USB hub connected between the USB device and USB sniffer and observe that the results are identical.
7. Repeat steps 1-6 with a composite device with non-HID device classes and verify that the non-HID functions are rejected, or the entire device is rejected.

All devices on the PSD KM blacklist were tested and are rejected as expected. The evaluator confirmed that the blacklist in place rejects all devices found in step 2.

Units Tested	AVS-4228, XDS441FX
Result	PASS

Test 2

Not applicable - "Configurable" has not been selected in the [ST]. Therefore, this evaluation activity is not applicable.

3.1.2 FDP_RDR_EXT.1 Re-Enumeration Device Rejection

3.1.2.1 FDP_RDR_EXT.1.1

The TSF shall reject any device that attempts to enumerate again as a different unauthorized device.

Application Note

This SFR should prevent devices that change their class from authorized to unauthorized, but cannot prevent malicious devices that use an authorized HID-class.

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this SFR.

TSS

The evaluator shall examine the TSS to verify that it describes how the TSF identifies and rejects a device that attempts to enumerate again as a different device.

Guidance

There are no guidance EAs for this component.

Test

The evaluator shall use a BadUSB, programmable keyboard, and/or USB Rubber Ducky as a malicious USB device to perform the following test:



Step 1: Ensure the TOE and the Operational Environment are configured in accordance with the operational guidance. Ensure the TOE is powered off and connect a USB sniffer between the TOE and a computer. Open the real-time hardware information console.

Step 2: Configure the malicious USB device as a HID-class device and to re-enumerate as a mass storage device.

Step 3: Connect the malicious USB device to the TOE KM peripheral interface.

Step 4: Power on the TOE and activate the re-enumeration after 1 minute.

Step 5: Verify device rejection per TOE guidance, the cessation of traffic passed in the USB sniffer, and the absence of the device and any new devices in the information console.

Step 6: Remove the malicious USB device and reconfigure as a HID-class device and to re-enumerate as a mass storage device.

Step 7: Connect the malicious USB device to the TOE KM peripheral interface and activate the reenumeration after 1 minute.

Step 8: Verify device rejection per TOE guidance, the cessation of traffic passed in the USB sniffer, and the absence of the device and any new devices in the information console.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.1.2.1 of [ST] discusses Keyboard and Mouse Enumeration. A USB keyboard is connected to the TOE keyboard host emulator through the console keyboard port. The keyboard host emulator is a microcontroller which enumerates the connected keyboard and verifies that it is a permitted device type.

The USB mouse is connected to the TOE mouse host emulator through the USB mouse port. The mouse host emulator is a microcontroller which enumerates the connected mouse and verifies that it is a permitted device type.

Section 9.1.2.4 of [ST] states “If a connected device attempts to re-enumerate as a different USB device type, it will be rejected by the TOE.”

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Test 1

1. Ensure the TOE and the Operational Environment are configured in accordance with the operational guidance. Ensure the TOE is powered off and connect a USB sniffer between the TOE and a computer. Open a real-time hardware information console.
2. Configure the malicious USB device as a HID-class device and to re-enumerate as a mass storage device.
3. Connect the malicious USB device to the TOE KM peripheral interface.
4. Power on the TOE and active the re-enumeration after 1 minute.
5. Verify device rejection per TOE guidance, the cessation traffic passed in the USB sniffer, and the absence of the device and any new device in the information console.
6. Remove the malicious USB device and reconfigure as a HID-class device and to re-enumerate as a mass storage device.
7. Connect the malicious USB device to the TOE KM peripheral interface and active the re-enumeration after 1 minute.
8. Verify device rejection per TOE guidance, the cessation of traffic passed in the USB sniffer, and the absence of the device and any new devices in the information console.



The evaluator configured the USB device accordingly to verify device rejection and ensured the TOE is properly enforcing security protocols.

Units Tested	AVS-4228, XDS441FX
Result	PASS

4 Selection-Based Requirements

4.1 User Data Protection (FDP)

4.1.1 FDP_CDS_EXT.1 Connected Displays Supported

4.1.1.1 FDP_CDS_EXT.1.1

The TSF shall support [selection: one connected display, multiple connected displays] at a time.

Application Note

This SFR must be claimed if "switching can be initiated only through express user action" is chosen as a selection for FDP_SWI_EXT.1 in the PSD PP.

If "peripheral devices using a guard" is selected in FDP_SWI_EXT.2.2 (from the PSD PP), then "multiple connected displays" must be selected in FDP_CDS_EXT.1.1.

Evaluation Activity

Isolation Document

There are no Isolation Document EAs for this component.

TSS

The evaluator shall examine the TSS and verify that it describes how many connected displays may be supported at a time.

Guidance

The evaluator shall examine the operational user guidance and verify that it describes how many displays are supported by the TOE.

Test

There are no test EAs for this component beyond what the PSD PP requires.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.1.3.1 of the [ST] indicates the display types. "The AVS-42216, XDS441 and XDS441FX devices accept any DisplayPort or HDMI display device at the video peripheral ports. The AVS-4228 accepts any HDMI display device at the video peripheral ports. The TOE does not support a wireless connection to a video display.

The AVS-4228 and AVS-42216 devices support two video displays. The XDS441 and XDS441FX isolators support only one display."

Guidance Evaluator Assessment:



Section 4.4 of the [CC_Supp] has a table (Table 2) that lists each device and the number of displays per device.

Test Evaluator Assessment:

Not applicable

4.1.2 FDP_IPC_EXT.1 Internal Protocol Conversion

4.1.2.1 FDP_IPC_EXT.1.1

The TSF shall convert the [DisplayPort] protocol at the [computer video interface] into the [HDMI] protocol within the TOE.

4.1.2.2 FDP_IPC_EXT.1.2

The TSF shall output the [HDMI] protocol from inside the TOE to [peripheral display interface(s)] as [selection: [DisplayPort] protocol, [HDMI] protocol].

Application Note

This SFR must be claimed if “DisplayPort” is chosen as a selection for FDP_PDC_EXT.2.1/VI.

Evaluation Activity

Isolation Document

There are no Isolation Document EAs for this component.

TSS

The evaluator shall examine the TSS and verify that it describes how data DisplayPort data is converted.

Guidance

There are no guidance EAs for this component.

Test

Testing for this SFR is covered under FDP_APC_EXT.1 Test 3-VI.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.1.3 of the [ST] discusses the video functionality in detail. In the discussion it states that “For DisplayPort connections, the TOE video function filters the AUX channel by converting it to I2C EDID only. DisplayPort video is converted into an HDMI video stream.”

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Not applicable

4.1.3 FDP_SWI_EXT.3 Tied Switching

4.1.3.1 FDP_SWI_EXT.3.1

The TSF shall ensure that [connected keyboard and mouse peripheral devices] are always switched together to the same connected



computer.

Application Note

This SFR must be claimed if "switching can be initiated only through express user action" is chosen as a selection for FDP_SWI_EXT.1.1 in the PSD PP and if both "USB (keyboard)" and "USB (mouse)" are chosen as selections in FDP_PDC_EXT.2.1/KM.

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this SFR.

TSS

The evaluator shall verify that the TSS does not indicate that keyboard and mouse devices may be switched independently to different connected computers.

Guidance

The evaluator shall verify that the guidance does not describe how to switch the keyboard and mouse devices independently to different connected computers.

Test

The evaluator shall verify that the keyboard and mouse devices are always switched together to the same connected computer throughout testing in FDP_APC_EXT.1 in [MOD_KM_SD] section 2.1.2 above.

Tests for this SFR are performed in FDP_APC_EXT.1 test 1-KM in [MOD_KM_V1.0_SD] section 2.1.2 above.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.1.2.2 of the [ST] discusses keyboard and mouse switching. It states that the keyboard and mouse can only be switched together.

Guidance Evaluator Assessment:

The evaluator verified that guidance documents do not describe the keyboard and mouse switching independently to a different computer.

Test Evaluator Assessment:

Not applicable

4.1.4 FDP_RIP.1/KM Residual Information Protection (Keyboard Data)

4.1.4.1 FDP_RIP.1.1/KM

The TSF shall ensure that any keyboard data in volatile memory is purged upon switching computers.

Application Note

This SFR must be claimed if "switching can be initiated only through express user action" is chosen as a selection for FDP_SWI_EXT.1.1 in the PSD PP and if "USB (keyboard)" is chosen as a selection in FDP_PDC_EXT.2.1/KM.

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this component.

TSS



The evaluator shall verify that the TSS indicates whether or not the TOE has user data buffers.

The evaluator shall verify that the TSS describes how all keyboard data stored in volatile memory is deleted upon switching computers.

Guidance

There are no guidance EAs for this component.

Test

There are no test EAs for this component.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.1.2.1 of the [ST] states “The Static Random Access Memory (SRAM) in the host and device emulator circuitry stores USB Host stack parameters and up to the last 4 key codes. User data may be briefly retained; however, there are no data buffers. Data is erased during power off of the device, and when the user switches channels (for the AVS-4228 and AVS-42216 devices). When the TOE switches from one computer to another, the system controller ensures that the keyboard and mouse stacks are deleted, and that any data received from the keyboard in the first 100 milliseconds following switching is deleted. This is done to ensure that any data buffered in the keyboard microcontroller is not passed to the newly selected computer.”

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Not applicable

4.1.5 FDP_SPR_EXT.1/DP Sub-Protocol Rules (DisplayPort Protocol)

4.1.5.1 FDP_SPR_EXT.1.1/DP

The TSF shall apply the following rules for the [DisplayPort] protocol:

- block the following video/display sub-protocols:

- o [CEC,*
- o EDID from computer to display,*
- o HDCP,*
- o MCCS]*

- allow the following video/display sub-protocols:

- o [EDID from display to computer,*
- o HPD from display to computer,*
- o Link Training].*

**Application Note**

The ST author must include this SFR if "DisplayPort" is selected in FDP_PDC_EXT.3.1/VI.

Evaluation Activity**Isolation Document**

There are no Isolation Document EAs for this component.

TSS

The evaluator shall examine the TSS and verify that it describes that the various sub-protocols are allowed or blocked by the TOE as described by the SFR.

Guidance

There are no guidance EAs for this component.

Test

Testing for this SFR is covered under FDP_APC_EXT.1 Test 3-VI and Test 4-VI.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.1.3 of the [ST] has a detailed discussion on the useable protocols by the display port.

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Not applicable

4.1.6 FDP_SPR_EXT.1/HDMI Sub-Protocol Rules (HDMI Protocol)**4.1.6.1 FDP_SPR_EXT.1.1/HDMI**

The TSF shall apply the following rules for the [HDMI] protocol:

- block the following video/display sub-protocols:

- o [ARC,
- o CEC,
- o EDID from computer to display,
- o HDCP,
- o HEAC,
- o HEC,
- o MCCS]

- allow the following video/display sub-protocols:



- o [EDID from display to computer,
- o HPD from display to computer].

Application Note

The ST author must include this SFR if "HDMI" is selected in FDP_PDC_EXT.3.1/VI.

Evaluation Activity

Isolation Document

There are no Isolation Document EAs for this component.

TSS

The evaluator shall examine the TSS and verify that it describes that the various sub-protocols are allowed or blocked by the TOE as described by the SFR.

Guidance

There are no guidance EAs for this component.

Test

Testing for this SFR is covered under FDP_APC_EXT.1 Test 3-VI and Test 4-VI.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.1.3 of the [ST] of has a detailed discussion on the protocols useable by the HDMI port.

Guidance Evaluator Assessment:

Not applicable

Test Evaluator Assessment:

Not applicable

4.1.7 FDP_SWI_EXT.2 PSD Switching Methods

4.1.7.1 FDP_SWI_EXT.2.1

The TSF shall ensure that no switching can be initiated through automatic port scanning, control through a connected computer, or control through keyboard shortcuts.

4.1.7.2 FDP_SWI_EXT.2.2

The TSF shall ensure that switching can be initiated only through express user action using [selection: console buttons, console switches, console touch screen, wired remote control, peripheral devices using a guard].

Application Note

This SFR must be claimed if "switching can be initiated only through express user action" is chosen as the selection for FDP_SWI_EXT.1.1.

If the TOE also claims conformance to the PP-Module for Video/Display Devices (Video Module) and if "peripheral devices using a guard" is selected here, the TOE must claim the selection-based requirement FDP_CDS_EXT.1 in the Video Module and select "multiple connected displays" in FDP_CDS_EXT.1.1.



Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this component.

TSS

The evaluator shall verify that the TSS describes the TOE supported switching mechanisms. The evaluator shall verify that the TSS does not include automatic port scanning, control through a connected computer, and control through keyboard shortcuts as TOE supported switching mechanisms. The evaluator shall verify that the described switching mechanisms can be initiated only through express user action according to the selections.

If "peripheral devices using a guard" is selected, the evaluator shall verify that the TSS describes the implementation of the guard function, and verify that multiple, simultaneous express user action is required to switch between connected computers using connected peripheral devices.

Guidance

The evaluator shall verify that the operational user guidance describes the TOE supported switching mechanisms. The evaluator shall verify that the operational user guidance does not include automatic port scanning, control through a connected computer, and control through keyboard shortcuts as TOE supported switching mechanisms.

If "peripheral devices using a guard" is selected, the evaluator shall verify that the user guidance describes the steps the user must take as required by the guard to switch between connected computers using a connected peripheral pointing device.

Test

[UA] Test performed in FDP_APC_EXT.1 above.

The evaluator shall ensure that switching is always initiated through express user action using the selected mechanisms throughout testing for FDP_APC_EXT.1 above.

Additional tests for this SFR are performed in FDP_APC_EXT.1 test 1-KM in section 2.1.2 above.

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

Section 9.1.1.1 AVS-4228 and AVS-42216 System Controller Functions of the [ST] states, "The user determines the host computer to be connected to the peripherals by pressing a button on the TOE front panel, or on the remote control. The front panel button of the selected computer is illuminated. When the remote control is used, both the front panel button and the remote-control channel indicator for the selected computer are illuminated. These are always consistent. Switching can only be initiated through express user action.

Additionally, TOE devices may be switched with peripheral devices using a guard. This is done by moving the mouse to the edge of the screen while pressing the left CTRL key."

Section 9.1.1.2 XDS441 and XDS441FX System Controller Functions states "The XDS441 and XDS441FX devices support only one connected computer."

Guidance Evaluator Assessment:

The [QS-000040] guide in the "Switching between computers" section explains the device switching mechanisms. [CC_Supp] section 4.6 explains the use of a guard.

Test Evaluator Assessment:

Not applicable



4.2 TOE Access (FTA)

4.2.1 FTA_CIN_EXT.1 Continuous Indications

This SFR is selection-based in the PSD PP. It remains selection-based when the TOE conforms to this PP Module. However, this PP-Module adds a trigger for its selection—specifically, if “multiple connected displays” is selected in FDP_CDS_EXT.1.1, then FTA_CIN_EXT.1 is applicable to the TOE and must be claimed.

The following SFR has a specific assignment, which is a mandatory selection if selecting “multiple connected displays” in FDP_CDS_EXT.1.1.

Additionally, the SFR is refined to specify an additional display mechanism in FTA_CIN_EXT.1.2

4.2.1.1 FTA_CIN_EXT.1.1

The TSF shall display a visible indication of the selected computers at all times when the TOE is powered.

4.2.1.2 FTA_CIN_EXT.1.2

The TSF shall implement the visible indication using the following mechanism: easily visible graphical and/or textual markings of each source video on the display, [selection: a button, a panel with lights, a screen with dimming function, a screen with no dimming function, [assignment: description of visible indication]].

4.2.1.3 FTA_CIN_EXT.1.3

The TSF shall ensure that while the TOE is powered the current switching status is reflected by [selection: the indicator, multiple indicators which never display conflicting information].

Application Note

This SFR must be claimed if “switching can be initiated only through express user action” is chosen as the selection for FDP_SWI_EXT.1.1.

FTA_CIN_EXT.1.3’s selection of “multiple indicators which never display conflicting information” should be selected when the TOE has multiple indicators, and concerns TOEs with multiple authorized switching mechanisms that have distinct switching status indicators. Such indicators must never convey conflicting information to the user regarding the currently selected interface(s). In general, all indicators must always reflect the same status. It is permissible for the most recently used switching mechanism to reflect the current status while all other indicators to reflect no status. It is also permissible for a TOE that supports split control (i.e., different peripherals pointing to different computers) to have separate indicators for individual peripherals. Note however that a TOE that supports keyboard/mouse peripherals is not permitted to have the keyboard and mouse peripherals split in this manner, as per the requirements in the PP-Module for Keyboard/Mouse (KM) Devices.

If multiple products with single and multiple indicators are part of the TOE, then it is recommended that FTA_CIN_EXT.1.3 be iterated for each selection rather than do a different evaluation for each model.

Evaluation Activity

Isolation Document

There are no Isolation Document evaluation activities for this component.

TSS

The evaluator shall verify that the TSS describes how the TOE behaves on power up and on reset, if applicable, regarding which computer interfaces are active, if any.

The evaluator shall verify that the TSS documents the behavior of all indicators when each switching mechanism is in use, and that no conflicting information is displayed by any indicators.

Guidance

The evaluator shall verify that the operational user guidance notes which computer connection is active on TOE power up or on



recovery from reset, if applicable. If a reset option is available, use of this feature must be described in the operational user guidance. The evaluator shall verify that the operational user guidance documents the behavior of all indicators when each switching mechanism is in use, and that no conflicting information is displayed by any indicators.

Test

Step 1: The evaluator shall configure the TOE and its operational environment in accordance with the operational user guidance.

Step 2: The evaluator shall select a connected computer and power down the TOE, then power up the TOE and verify that the expected selected computer is indicated in accordance with the TSS and that the connection is active.

Step 3: The evaluator shall repeat this process for every possible selected TOE configuration.

Step 4: [Conditional] If "upon reset button activation" is selected in FPT_TST.1.1, then the evaluator shall repeat this process for each TOE configuration using the reset function rather than power-down and powerup.

Step 5: The evaluator shall verify that the TOE selected computer indications are always on (i.e., continuous) and fully visible to the TOE user.

Step 6: [Conditional] If the TOE allows peripherals to have active interfaces with different computers at the same time, the evaluator shall verify that each permutation has its own selection indications.

Step 7: [Conditional] If "a screen with dimming function" is selected, the evaluator shall verify that indications are visible at minimum brightness settings in standard room illumination conditions.

Step 8: [Conditional] If "multiple indicators which never display conflicting information" is selected, the evaluator shall verify that either all indicators reflect the same status at all times, or the indicator for the most recently used switching mechanism displays the correct switching status and that all other indicators display the correct status or no status.

[VI] Additional testing for this component is performed in test 1-VI of FDP_APC_EXT.1 in section 2.1.3 above.

Evaluator note: This is a reference to [MOD_VI_SD]

Isolation Document Evaluator Assessment:

Not applicable

TSS Evaluator Assessment:

The [ST] section and 9.3.1 all describes the power up behavior. "The TOE user switches between computers by pressing the corresponding front panel button on the device or on the remote control, or by using the mouse with a guard. The front panel button corresponding to the selected computer will illuminate. The button on the remote control corresponding to the selected computer will also illuminate. On power up, all peripherals are connected to channel #1, and the corresponding push button LED will be illuminated."

Guidance Evaluator Assessment:

Section 4.3 of the [CC_Supp] states "Channel 1 is selected by default when the peripheral sharing device is started"

Test Evaluator Assessment:

Test 1

Note: This SFR is only selected for the AVS-4228 therefore this test was only performed on that device.

1. The evaluator configured the TOE and its operational environment in accordance with the operational user guidance.
2. The evaluator selected a connected computer and powered down the TOE, then powered up the TOE and verified that the expected selected computer is indicated in accordance with the TSS and that the connection is active.



3. The evaluator repeated this process for every possible selected TOE configuration.
4. [Conditional] If “*upon reset button activation*” is selected in FPT_TST.1.1, then the evaluator repeated this process for each TOE configuration using the reset function rather than power-down and power-up.
5. The evaluator verified that the TOE selected computer indications are always on (i.e., continuous) and fully visible to the TOE user.
6. [Conditional] The TOE does not match the condition. In [ST], “If the TOE allows peripherals to have active interfaces with different computers at the same time” is not selected. Therefore, this test step is not applicable.
7. [Conditional] The TOE does not match the condition. In [ST], “*a screen with dimming function*” is not selected. Therefore, this test step is not applicable.
8. [Conditional] “*multiple indicators which never display conflicting information*” is selected. The evaluator verified that the indicator for the most recently used switching mechanism displays the correct switching status and that all other indicators display the correct status or no status.

The evaluator confirmed the TOE properly indicates which computer connection is active on TOE power up. The evaluator also verified the behavior of all indicators when each switching mechanism is in use, and that no conflicting information is displayed by any indicators.

Units Tested	AVS-4228
Result	PASS

5 Security Assurance Requirement Activities

5.1 Development (ADV)

5.1.1 ADV_FSP.1 Basic Functional Specifications

Evaluation Activity

There are no specific Evaluation Activities associated with these SARs. The Evaluation Activities listed in this PP are associated with the applicable SFRs; since these are directly associated with the SFRs, the tracing element ADV_FSP.1.2D is implicitly already done, and no additional documentation is necessary. The functional specification documentation is provided to support the evaluation activities described in Section 5.2 and other activities described for AGD, and ATE SARs. The requirements on the content of the functional specification information are implicitly assessed by virtue of the other Evaluation Activities being performed. If the evaluator is unable to perform an activity because there is insufficient interface information, then an adequate functional specification has not been provided.

Evaluator Assessment:

The [ST] TSS and [CC_Supp] were used to derive the verdicts for ADV_FSP.1. The FDP_PDC_EXT.1.4 TSS Evaluation activity identifies the security relevant external interfaces of the TOE.

5.2 Guidance Documents (AGD)

5.2.1 AGD_OPE.1 Operational User Guidance

Evaluation Activity

The operational user guidance does not have to be contained in a single document. Guidance to users and Administrators can be spread among documents or web pages. The developer should review the Evaluation Activities contained in Section 5.2 of this PP to



ascertain the specifics of the guidance for which the evaluator will be checking. This will provide the necessary information for the preparation of acceptable guidance.

Evaluator Assessment:

The guidance documentation consists of Quick Start Guides [QS-000040], [QS-000045], [QS-000047] and a [CC_Supp]. These provide the information to assess the AGD_OPE.1 assessments. The guidance documents describe modes of operation, fail states, and procedures for the TOE's usage and operational environment.

5.2.2 AGD_PRE.1 Preparative Procedures

Evaluation Activity

As with the operational user guidance, the developer should look to the Evaluation Activities contained in Section 5.2 of this PP to determine the required content with respect to preparative procedures.

Evaluator Assessment:

The [CC_Supp] provides acceptance procedures and instructions for preparation of the operational environment. [QS-000040], [QS-000045] and [QS-000047] provide clear installation procedures.

5.3 Life-Cycle Support (ALC)

5.3.1 ALC_CMC.1 Labeling of the TOE

Note

This component is targeted at identifying the TOE such that it can be distinguished from other products or versions from the same vendor and can be easily specified when being procured by an end user.

A label should consist of a "hard label" (e.g., stamped into the metal, paper label) or a "soft label" (e.g., electronically presented when queried).

The evaluator performs the CEM work units associated with ALC_CMC.1, as well as the Evaluation Activity specified below.

Evaluation Activity

The "evaluation evidence required by the SARs" in this PP is limited to the information in the ST coupled with the guidance provided to administrators and users under the AGD requirements. By ensuring that the TOE is specifically identified and that this identification is consistent in the ST and in the AGD guidance, the evaluator implicitly confirms the information required by this component.

Evaluator Assessment:

The ST was used to determine the TOE identification and hence verdicts for ALC_CMC.1. The labeling on the guidance documents and nameplate on the underside of the TOE were consistent with the identification of the TOE.

5.3.2 ALC_CMS.1 TOE CM Coverage

Evaluation Activity

Given the scope of the TOE and its associated evaluation evidence requirements, this component's Evaluation Activities are covered by the Evaluation Activities listed for ALC_CMC.1.

Evaluator Assessment:

NA – covered under ALC_CMC.1



5.4 Tests (ATE)

5.4.1 ATE_IND Independent Testing - Conformance

Evaluation Activity

The evaluator shall prepare a test plan and report documenting the testing aspects of the system. The test plan covers all of the testing actions contained in the CEM and the body of this PP's Evaluation Activities. While it is not necessary to have one test case per test listed in an Evaluation Activity, the evaluator must document in the test plan that each applicable testing requirement in the PP is covered.

The test plan identifies the platforms to be tested, and for those platforms not included in the test plan but included in the ST, the test plan provides a justification for not testing the platforms. This justification must address the differences between the tested platforms and the untested platforms and make an argument that the differences do not affect the testing to be performed. It is not sufficient to merely assert that the differences have no affect; rationale must be provided. If all platforms claimed in the ST are tested, then no rationale is necessary.

The test plan describes the composition of each platform to be tested and any setup that is necessary beyond what is contained in the AGD documentation. It should be noted that the evaluator is expected to follow the AGD documentation for installation and setup of each platform either as part of a test or as a standard pre-test condition. This may include special test equipment or tools. For each piece of equipment or tool, an argument (not just an assertion) should be provided that the equipment or tool will not adversely affect the performance of the functionality by the TOE and its platform.

The test plan identifies high-level test objectives as well as the test procedures to be followed to achieve those objectives. These procedures include expected results. The test report (which could just be an annotated version of the test plan) details the activities that took place when the test procedures were executed, and includes the actual results of the tests. This shall be a cumulative account, so if there was a test run that resulted in a failure; a fix installed; and then a successful re-run of the test, the report would show a "fail" and "pass" result (and the supporting details), and not just the "pass" result.

Evaluator Assessment:

The evaluator tested the devices according to the tests in the PP and its modules. The setup was done according to the [CC_Supp] and the Quick Start Guides. The test cases were run successfully with pass verdicts recorded in the [ETProcRes]. The evaluation verdicts for the ATE class are in the ETR.

5.5 Vulnerability Analysis (AVA)

5.5.1 AVA_VAN.1 Vulnerability Survey

Evaluation Activity

As with ATE_IND, the evaluator shall generate a report to document their findings with respect to this requirement. This report could physically be part of the overall test report mentioned in ATE_IND, or a separate document. The evaluator performs a search of public information to determine the vulnerabilities that have been found in peripheral sharing devices and the implemented communication protocols in general, as well as those that pertain to the particular TOE. The evaluator documents the sources consulted and the vulnerabilities found in the report. For each vulnerability found, the evaluator either provides a rationale with respect to its non-applicability, or the evaluator formulates a test (using the guidelines provided in ATE_IND) to confirm the vulnerability, if suitable. Suitability is determined by assessing the attack vector needed to take advantage of the vulnerability. If exploiting the vulnerability requires expert skills and an electron microscope, for instance, then a test would not be suitable and an appropriate justification would be formulated.

Evaluator Assessment:

The evaluator conducted a vulnerability assessment. The TOE is not connected to the Internet so no penetration tests were conducted. A vulnerability scan and search was conducted. This was recorded in the test plan [ETProcRes]. No vulnerabilities were found.